

■ 6) デッキ型枠時の許容スパン (K P - 1 - 0.8mm (AKD08))

軽量コン(kN/m<sup>2</sup>) ; 20 F=205 (N/mm<sup>2</sup>)

コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	22.0	1,999	1,740	2,340	2,160
20	32.0	2,199	1,690	2,260	2,090
30	42.0	2,399	1,640	2,200	2,030
40	52.0	2,599	1,600	2,140	1,970
50	62.0	2,799	1,560	2,090	1,930
60	72.0	2,999	1,520	2,040	1,880
70	82.0	3,199	1,490	2,000	1,840
80	92.0	3,399	1,460	1,960	1,800
90	102.0	3,599	1,430	1,920	1,770
100	112.0	3,799	1,410	1,890	1,740
110	122.0	3,999	1,380	1,850	1,710
120	132.0	4,199	1,360	1,820	1,680
130	142.0	4,399	1,340	1,800	1,660
140	152.0	4,599	1,320	1,770	1,630
150	162.0	4,799	1,300	1,740	1,610
160	172.0	4,999	1,280	1,720	1,590
170	182.0	5,199	1,270	1,700	1,570
180	192.0	5,399	1,250	1,680	1,550
190	202.0	5,599	1,230	1,660	1,530
200	212.0	5,799	1,220	1,640	1,510
210	222.0	5,999	1,210	1,620	1,490
220	232.0	6,199	1,190	1,600	1,480
230	242.0	6,399	1,180	1,580	1,460
240	252.0	6,599	1,170	1,560	1,450
250	262.0	6,799	1,160	1,530	1,430
260	272.0	6,999	1,150	1,510	1,420
270	282.0	7,199	1,140	1,490	1,400
280	292.0	7,399	1,120	1,470	1,390
290	302.0	7,599	1,110	1,450	1,380
300	312.0	7,799	1,110	1,430	1,370
310	322.0	7,999	1,100	1,410	1,360
320	332.0	8,199	1,090	1,400	1,340
330	342.0	8,399	1,080	1,380	1,330
340	352.0	8,599	1,070	1,360	1,320
350	362.0	8,799	1,060	1,350	1,310
360	372.0	8,999	1,050	1,330	1,300
370	382.0	9,199	1,050	1,320	1,290
380	392.0	9,399	1,040	1,300	1,280
390	402.0	9,599	1,030	1,290	1,280
400	412.0	9,799	1,020	1,280	1,270
410	422.0	9,999	1,020	1,260	1,260
420	432.0	10,199	1,010	1,250	1,250
430	442.0	10,399	1,000	1,240	1,240
440	452.0	10,599	1,000	1,230	1,230
450	462.0	10,799	990	1,210	1,230
460	472.0	10,999	980	1,200	1,220
470	482.0	11,199	980	1,190	1,210
480	492.0	11,399	970	1,180	1,200
490	502.0	11,599	970	1,170	1,200
500	512.0	11,799	960	1,160	1,190
510	522.0	11,999	960	1,150	1,180
520	532.0	12,199	950	1,140	1,180
530	542.0	12,399	950	1,130	1,170
540	552.0	12,599	940	1,120	1,160
550	562.0	12,799	940	1,120	1,160
560	572.0	12,999	930	1,110	1,150
570	582.0	13,199	930	1,100	1,150
580	592.0	13,399	920	1,090	1,140
590	602.0	13,599	920	1,080	1,130
600	612.0	13,799	910	1,070	1,130

■ 8) デッキ型枠時の許容スパン (K P - 1 - 1.2mm (AKD12))

軽量コン(kN/m<sup>2</sup>) ; 20 F=205 (N/mm<sup>2</sup>)

コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	22.0	2,040	1,950	2,620	2,410
20	32.0	2,240	1,890	2,540	2,340
30	42.0	2,440	1,840	2,470	2,270
40	52.0	2,640	1,790	2,400	2,220
50	62.0	2,840	1,750	2,350	2,160
60	72.0	3,040	1,710	2,290	2,110
70	82.0	3,240	1,670	2,240	2,070
80	92.0	3,440	1,640	2,200	2,030
90	102.0	3,640	1,610	2,160	1,990
100	112.0	3,840	1,580	2,120	1,950
110	122.0	4,040	1,550	2,080	1,920
120	132.0	4,240	1,530	2,050	1,890
130	142.0	4,440	1,510	2,020	1,860
140	152.0	4,640	1,480	1,990	1,830
150	162.0	4,840	1,460	1,960	1,810
160	172.0	5,040	1,440	1,940	1,780
170	182.0	5,240	1,420	1,910	1,760
180	192.0	5,440	1,410	1,890	1,740
190	202.0	5,640	1,390	1,860	1,720
200	212.0	5,840	1,370	1,840	1,700
210	222.0	6,040	1,360	1,820	1,680
220	232.0	6,240	1,340	1,800	1,660
230	242.0	6,440	1,330	1,780	1,640
240	252.0	6,640	1,320	1,770	1,630
250	262.0	6,840	1,300	1,750	1,610
260	272.0	7,040	1,290	1,730	1,600
270	282.0	7,240	1,280	1,720	1,580
280	292.0	7,440	1,270	1,700	1,570
290	302.0	7,640	1,260	1,680	1,550
300	312.0	7,840	1,240	1,670	1,540
310	322.0	8,040	1,230	1,660	1,530
320	332.0	8,240	1,220	1,640	1,510
330	342.0	8,440	1,210	1,630	1,500
340	352.0	8,640	1,200	1,620	1,490
350	362.0	8,840	1,200	1,600	1,480
360	372.0	9,040	1,190	1,590	1,470
370	382.0	9,240	1,180	1,570	1,460
380	392.0	9,440	1,170	1,550	1,450
390	402.0	9,640	1,160	1,540	1,440
400	412.0	9,840	1,150	1,520	1,430
410	422.0	10,040	1,150	1,510	1,420
420	432.0	10,240	1,140	1,490	1,410
430	442.0	10,440	1,130	1,480	1,400
440	452.0	10,640	1,120	1,460	1,390
450	462.0	10,840	1,120	1,450	1,380
460	472.0	11,040	1,110	1,440	1,370
470	482.0	11,240	1,100	1,420	1,360
480	492.0	11,440	1,100	1,410	1,360
490	502.0	11,640	1,090	1,400	1,350
500	512.0	11,840	1,080	1,390	1,340
510	522.0	12,040	1,080	1,380	1,330
520	532.0	12,240	1,070	1,360	1,330
530	542.0	12,440	1,070	1,350	1,320
540	552.0	12,640	1,060	1,340	1,310
550	562.0	12,840	1,060	1,330	1,310
560	572.0	13,040	1,050	1,320	1,300
570	582.0	13,240	1,040	1,310	1,290
580	592.0	13,440	1,040	1,300	1,290
590	602.0	13,640	1,030	1,290	1,280
600	612.0	13,840	1,030	1,280	1,270