

■ 2) デッキ型枠時の許容スパン (K P - 1 - 0.8mm (AKD08))

普通コン(kN/m²) ; 24 F=205 (N/mm²)

コン厚さ (mm)	溝コン厚さ 12	総荷重 (N/m ²)	単純 許容スパン	2連続 許容スパン	3連続 許容スパン
10	22.0	2,087	1,720	2,300	2,120
20	32.0	2,327	1,660	2,220	2,050
30	42.0	2,567	1,600	2,150	1,980
40	52.0	2,807	1,560	2,090	1,920
50	62.0	3,047	1,510	2,030	1,870
60	72.0	3,287	1,480	1,980	1,830
70	82.0	3,527	1,440	1,930	1,780
80	92.0	3,767	1,410	1,890	1,740
90	102.0	4,007	1,380	1,850	1,710
100	112.0	4,247	1,350	1,820	1,680
110	122.0	4,487	1,330	1,780	1,640
120	132.0	4,727	1,310	1,750	1,620
130	142.0	4,967	1,290	1,720	1,590
140	152.0	5,207	1,270	1,700	1,560
150	162.0	5,447	1,250	1,670	1,540
160	172.0	5,687	1,230	1,650	1,520
170	182.0	5,927	1,210	1,630	1,500
180	192.0	6,167	1,200	1,600	1,480
190	202.0	6,407	1,180	1,580	1,460
200	212.0	6,647	1,170	1,550	1,440
210	222.0	6,887	1,150	1,520	1,430
220	232.0	7,127	1,140	1,500	1,410
230	242.0	7,367	1,130	1,470	1,390
240	252.0	7,607	1,110	1,450	1,380
250	262.0	7,847	1,100	1,430	1,360
260	272.0	8,087	1,090	1,400	1,350
270	282.0	8,327	1,080	1,380	1,340
280	292.0	8,567	1,070	1,360	1,320
290	302.0	8,807	1,060	1,350	1,310
300	312.0	9,047	1,050	1,330	1,300
310	322.0	9,287	1,040	1,310	1,290
320	332.0	9,527	1,030	1,290	1,280
330	342.0	9,767	1,020	1,280	1,270
340	352.0	10,007	1,020	1,260	1,260
350	362.0	10,247	1,010	1,250	1,250
360	372.0	10,487	1,000	1,230	1,240
370	382.0	10,727	990	1,220	1,230
380	392.0	10,967	990	1,210	1,220
390	402.0	11,207	980	1,190	1,210
400	412.0	11,447	970	1,180	1,200
410	422.0	11,687	970	1,170	1,190
420	432.0	11,927	960	1,160	1,190
430	442.0	12,167	950	1,140	1,180
440	452.0	12,407	950	1,130	1,170
450	462.0	12,647	940	1,120	1,160
460	472.0	12,887	930	1,110	1,160
470	482.0	13,127	930	1,100	1,150
480	492.0	13,367	920	1,090	1,140
490	502.0	13,607	920	1,080	1,130
500	512.0	13,847	910	1,070	1,130
510	522.0	14,087	910	1,060	1,120
520	532.0	14,327	900	1,050	1,120
530	542.0	14,567	900	1,050	1,110
540	552.0	14,807	890	1,040	1,100
550	562.0	15,047	890	1,030	1,100
560	572.0	15,287	880	1,020	1,090
570	582.0	15,527	880	1,010	1,090
580	592.0	15,767	870	1,000	1,080
590	602.0	16,007	870	1,000	1,070
600	612.0	16,247	860	990	1,070

■ 4) デッキ型枠時の許容スパン (K P - 1 - 1.2mm (AKD12))

普通コン(kN/m²) ; 24 F=205 (N/mm²)

コン厚さ (mm)	溝コン厚さ 12	総荷重 (N/m ²)	単純 許容スパン	2連続 許容スパン	3連続 許容スパン
10	22.0	2,128	1,930	2,580	2,380
20	32.0	2,368	1,860	2,490	2,300
30	42.0	2,608	1,800	2,410	2,220
40	52.0	2,848	1,750	2,340	2,160
50	62.0	3,088	1,700	2,280	2,100
60	72.0	3,328	1,660	2,220	2,050
70	82.0	3,568	1,620	2,170	2,000
80	92.0	3,808	1,580	2,130	1,960
90	102.0	4,048	1,550	2,080	1,920
100	112.0	4,288	1,520	2,040	1,880
110	122.0	4,528	1,500	2,010	1,850
120	132.0	4,768	1,470	1,970	1,820
130	142.0	5,008	1,450	1,940	1,790
140	152.0	5,248	1,420	1,910	1,760
150	162.0	5,488	1,400	1,880	1,730
160	172.0	5,728	1,380	1,860	1,710
170	182.0	5,968	1,360	1,830	1,690
180	192.0	6,208	1,350	1,810	1,660
190	202.0	6,448	1,330	1,780	1,640
200	212.0	6,688	1,310	1,760	1,620
210	222.0	6,928	1,300	1,740	1,600
220	232.0	7,168	1,280	1,720	1,590
230	242.0	7,408	1,270	1,700	1,570
240	252.0	7,648	1,260	1,680	1,550
250	262.0	7,888	1,240	1,670	1,540
260	272.0	8,128	1,230	1,650	1,520
270	282.0	8,368	1,220	1,630	1,510
280	292.0	8,608	1,210	1,620	1,490
290	302.0	8,848	1,200	1,600	1,480
300	312.0	9,088	1,180	1,580	1,470
310	322.0	9,328	1,170	1,560	1,450
320	332.0	9,568	1,160	1,540	1,440
330	342.0	9,808	1,150	1,520	1,430
340	352.0	10,048	1,150	1,510	1,420
350	362.0	10,288	1,140	1,490	1,410
360	372.0	10,528	1,130	1,470	1,400
370	382.0	10,768	1,120	1,460	1,380
380	392.0	11,008	1,110	1,440	1,370
390	402.0	11,248	1,100	1,420	1,360
400	412.0	11,488	1,100	1,410	1,360
410	422.0	11,728	1,090	1,390	1,350
420	432.0	11,968	1,080	1,380	1,340
430	442.0	12,208	1,070	1,370	1,330
440	452.0	12,448	1,070	1,350	1,320
450	462.0	12,688	1,060	1,340	1,310
460	472.0	12,928	1,050	1,330	1,300
470	482.0	13,168	1,050	1,320	1,290
480	492.0	13,408	1,040	1,300	1,290
490	502.0	13,648	1,030	1,290	1,280
500	512.0	13,888	1,030	1,280	1,270
510	522.0	14,128	1,020	1,270	1,260
520	532.0	14,368	1,020	1,260	1,260
530	542.0	14,608	1,010	1,250	1,250
540	552.0	14,848	1,010	1,240	1,240
550	562.0	15,088	1,000	1,230	1,240
560	572.0	15,328	990	1,220	1,230
570	582.0	15,568	990	1,210	1,220
580	592.0	15,808	980	1,200	1,220
590	602.0	16,048	980	1,190	1,210
600	612.0	16,288	970	1,180	1,210