

■ 1) デッキ型枠時の許容スパン (MA 5 0 - 1.0mm)

普通コン(kN/m <sup>2</sup> ): 24		F=235 (N/mm <sup>2</sup> )			
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	25.1	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	35.1	2,440	2,730	3,640	3,360
20	45.1	2,680	2,640	3,530	3,260
30	55.1	2,920	2,570	3,430	3,170
40	65.1	3,160	2,500	3,350	3,080
50	75.1	3,400	2,440	3,260	3,010
60	85.1	3,640	2,380	3,190	2,940
70	95.1	3,880	2,330	3,120	2,880
80	105.1	4,120	2,290	3,060	2,820
85	110.1	4,240	2,270	3,030	2,800
90	115.1	4,360	2,250	3,000	2,770
95	120.1	4,480	2,230	2,980	2,740
100	125.1	4,600	2,210	2,950	2,720
110	135.1	4,840	2,170	2,900	2,670
120	145.1	5,080	2,130	2,850	2,630
130	155.1	5,320	2,100	2,790	2,590
140	165.1	5,560	2,070	2,730	2,550
150	175.1	5,800	2,040	2,670	2,520
160	185.1	6,040	2,010	2,620	2,480
170	195.1	6,280	1,990	2,570	2,450
180	205.1	6,520	1,960	2,520	2,420
190	215.1	6,760	1,940	2,470	2,390
200	225.1	7,000	1,920	2,430	2,360
210	235.1	7,240	1,900	2,390	2,340
220	245.1	7,480	1,870	2,350	2,310
230	255.1	7,720	1,860	2,310	2,290
240	265.1	7,960	1,840	2,280	2,270
250	275.1	8,200	1,820	2,250	2,240
260	285.1	8,440	1,800	2,210	2,220
270	295.1	8,680	1,780	2,180	2,200
280	305.1	8,920	1,770	2,150	2,180
290	315.1	9,160	1,750	2,120	2,160
300	325.1	9,400	1,740	2,100	2,140
310	335.1	9,640	1,720	2,070	2,120
320	345.1	9,880	1,710	2,050	2,110
330	355.1	10,120	1,690	2,020	2,090
340	365.1	10,360	1,680	2,000	2,070
350	375.1	10,600	1,670	1,970	2,060
360	385.1	10,840	1,660	1,950	2,040
370	395.1	11,080	1,640	1,930	2,030
380	405.1	11,320	1,630	1,910	2,010
390	415.1	11,560	1,620	1,890	2,000
400	425.1	11,800	1,610	1,870	1,990
410	435.1	12,040	1,600	1,850	1,970
420	445.1	12,280	1,590	1,830	1,960
430	455.1	12,520	1,580	1,820	1,950
440	465.1	12,760	1,570	1,800	1,930
450	475.1	13,000	1,560	1,780	1,920
460	485.1	13,240	1,550	1,770	1,910
470	495.1	13,480	1,540	1,750	1,900
480	505.1	13,720	1,530	1,740	1,890
490	515.1	13,960	1,520	1,720	1,880
500	525.1	14,200	1,510	1,710	1,870
510	535.1	14,440	1,500	1,690	1,860
520	545.1	14,680	1,500	1,680	1,850
530	555.1	14,920	1,490	1,660	1,840
540	565.1	15,160	1,480	1,650	1,830
550	575.1	15,400	1,470	1,640	1,820
560	585.1	15,640	1,470	1,620	1,810
570	595.1	15,880	1,460	1,610	1,800
580	605.1	16,120	1,450	1,600	1,790
590	615.1	16,360	1,440	1,590	1,780
600	625.1	16,600	1,440	1,580	1,760

■ 2) デッキ型枠時の許容スパン (MA 5 0 - 1.0mm)

軽量コン(kN/m <sup>2</sup> ): 20		F=235 (N/mm <sup>2</sup> )			
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	25.1	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	35.1	2,299	2,770	3,690	3,430
20	45.1	2,499	2,700	3,610	3,340
30	55.1	2,699	2,630	3,530	3,250
40	65.1	2,899	2,570	3,440	3,170
50	75.1	3,099	2,510	3,370	3,100
60	85.1	3,299	2,460	3,300	3,040
70	95.1	3,499	2,410	3,230	2,980
80	105.1	3,699	2,370	3,170	2,930
85	110.1	3,799	2,350	3,150	2,900
90	115.1	3,899	2,330	3,120	2,870
95	120.1	3,999	2,310	3,090	2,850
100	125.1	4,099	2,290	3,070	2,830
110	135.1	4,299	2,250	3,020	2,780
120	145.1	4,499	2,220	2,970	2,740
130	155.1	4,699	2,180	2,930	2,700
140	165.1	4,899	2,150	2,890	2,660
150	175.1	5,099	2,130	2,850	2,630
160	185.1	5,299	2,100	2,800	2,590
170	195.1	5,499	2,070	2,740	2,560
180	205.1	5,699	2,050	2,690	2,530
190	215.1	5,899	2,020	2,650	2,500
200	225.1	6,099	2,000	2,600	2,480
210	235.1	6,299	1,980	2,560	2,450
220	245.1	6,499	1,960	2,520	2,420
230	255.1	6,699	1,940	2,490	2,400
240	265.1	6,899	1,920	2,450	2,380
250	275.1	7,099	1,900	2,410	2,350
260	285.1	7,299	1,890	2,380	2,330
270	295.1	7,499	1,870	2,350	2,310
280	305.1	7,699	1,850	2,320	2,290
290	315.1	7,899	1,840	2,290	2,270
300	325.1	8,099	1,820	2,260	2,250
310	335.1	8,299	1,810	2,230	2,230
320	345.1	8,499	1,790	2,210	2,220
330	355.1	8,699	1,780	2,180	2,200
340	365.1	8,899	1,760	2,160	2,180
350	375.1	9,099	1,750	2,130	2,170
360	385.1	9,299	1,740	2,110	2,150
370	395.1	9,499	1,730	2,090	2,140
380	405.1	9,699	1,710	2,060	2,120
390	415.1	9,899	1,700	2,040	2,110
400	425.1	10,099	1,690	2,020	2,090
410	435.1	10,299	1,680	2,000	2,080
420	445.1	10,499	1,670	1,980	2,070
430	455.1	10,699	1,660	1,970	2,050
440	465.1	10,899	1,650	1,950	2,040
450	475.1	11,099	1,640	1,930	2,030
460	485.1	11,299	1,630	1,910	2,020
470	495.1	11,499	1,620	1,900	2,000
480	505.1	11,699	1,610	1,880	1,990
490	515.1	11,899	1,600	1,860	1,980
500	525.1	12,099	1,590	1,850	1,970
510	535.1	12,299	1,580	1,830	1,960
520	545.1	12,499	1,580	1,820	1,950
530	555.1	12,699	1,570	1,800	1,940
540	565.1	12,899	1,560	1,790	1,930
550	575.1	13,099	1,550	1,780	1,920
560	585.1	13,299	1,540	1,760	1,910
570	595.1	13,499	1,540	1,750	1,900
580	605.1	13,699	1,530	1,740	1,890
590	615.1	13,899	1,520	1,720	1,880
600	625.1	14,099	1,510	1,710	1,870