

■ 1) デッキ型枠時の許容スパン (MA 5 0 -1.2mm)

普通コン(kN/m <sup>2</sup> ): 24			F=235 (N/mm <sup>2</sup> )		
コ/厚さ	溝コ/厚さ	総荷重	単純	2連続	3連続
(mm)	25.1	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	35.1	2,440	2,890	3,810	3,580
20	45.1	2,680	2,800	3,720	3,460
30	55.1	2,920	2,720	3,640	3,370
40	65.1	3,160	2,650	3,560	3,280
50	75.1	3,400	2,590	3,470	3,200
60	85.1	3,640	2,530	3,390	3,130
70	95.1	3,880	2,480	3,320	3,060
80	105.1	4,120	2,430	3,260	3,000
85	110.1	4,240	2,400	3,220	2,970
90	115.1	4,360	2,380	3,190	2,950
95	120.1	4,480	2,360	3,170	2,920
100	125.1	4,600	2,340	3,140	2,890
110	135.1	4,840	2,300	3,090	2,840
120	145.1	5,080	2,260	3,040	2,800
130	155.1	5,320	2,230	2,990	2,760
140	165.1	5,560	2,200	2,950	2,720
150	175.1	5,800	2,170	2,900	2,680
160	185.1	6,040	2,140	2,870	2,640
170	195.1	6,280	2,110	2,820	2,610
180	205.1	6,520	2,080	2,760	2,570
190	215.1	6,760	2,060	2,710	2,540
200	225.1	7,000	2,030	2,670	2,510
210	235.1	7,240	2,010	2,620	2,490
220	245.1	7,480	1,990	2,580	2,460
230	255.1	7,720	1,970	2,540	2,430
240	265.1	7,960	1,950	2,500	2,410
250	275.1	8,200	1,930	2,460	2,390
260	285.1	8,440	1,910	2,430	2,360
270	295.1	8,680	1,890	2,400	2,340
280	305.1	8,920	1,880	2,360	2,320
290	315.1	9,160	1,860	2,330	2,300
300	325.1	9,400	1,840	2,300	2,280
310	335.1	9,640	1,830	2,270	2,260
320	345.1	9,880	1,810	2,240	2,240
330	355.1	10,120	1,800	2,220	2,220
340	365.1	10,360	1,780	2,190	2,210
350	375.1	10,600	1,770	2,170	2,190
360	385.1	10,840	1,760	2,140	2,170
370	395.1	11,080	1,740	2,120	2,160
380	405.1	11,320	1,730	2,100	2,140
390	415.1	11,560	1,720	2,070	2,130
400	425.1	11,800	1,710	2,050	2,110
410	435.1	12,040	1,700	2,030	2,100
420	445.1	12,280	1,690	2,010	2,080
430	455.1	12,520	1,670	1,990	2,070
440	465.1	12,760	1,660	1,970	2,060
450	475.1	13,000	1,650	1,960	2,040
460	485.1	13,240	1,640	1,940	2,030
470	495.1	13,480	1,630	1,920	2,020
480	505.1	13,720	1,620	1,900	2,010
490	515.1	13,960	1,610	1,890	2,000
500	525.1	14,200	1,610	1,870	1,990
510	535.1	14,440	1,600	1,860	1,970
520	545.1	14,680	1,590	1,840	1,960
530	555.1	14,920	1,580	1,830	1,950
540	565.1	15,160	1,570	1,810	1,940
550	575.1	15,400	1,560	1,800	1,930
560	585.1	15,640	1,550	1,780	1,920
570	595.1	15,880	1,550	1,770	1,910
580	605.1	16,120	1,540	1,760	1,900
590	615.1	16,360	1,530	1,740	1,890
600	625.1	16,600	1,520	1,730	1,880

■ 2) デッキ型枠時の許容スパン (MA 5 0 -1.6mm)

普通コン(kN/m <sup>2</sup> ): 24			F=235 (N/mm <sup>2</sup> )		
コ/厚さ	溝コ/厚さ	総荷重	単純	2連続	3連続
(mm)	24.8	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	34.8	2,474	3,150	4,050	3,810
20	44.8	2,714	3,050	3,960	3,730
30	54.8	2,954	2,970	3,880	3,650
40	64.8	3,194	2,890	3,800	3,570
50	74.8	3,434	2,820	3,740	3,490
60	84.8	3,674	2,760	3,670	3,410
70	94.8	3,914	2,700	3,610	3,340
80	104.8	4,154	2,650	3,550	3,270
85	109.8	4,274	2,620	3,520	3,240
90	114.8	4,394	2,600	3,480	3,210
95	119.8	4,514	2,570	3,450	3,180
100	124.8	4,634	2,550	3,420	3,160
110	134.8	4,874	2,510	3,370	3,100
120	144.8	5,114	2,470	3,310	3,050
130	154.8	5,354	2,430	3,260	3,010
140	164.8	5,594	2,400	3,210	2,960
150	174.8	5,834	2,360	3,170	2,920
160	184.8	6,074	2,330	3,130	2,880
170	194.8	6,314	2,300	3,090	2,850
180	204.8	6,554	2,270	3,050	2,810
190	214.8	6,794	2,250	3,010	2,780
200	224.8	7,034	2,220	2,980	2,750
210	234.8	7,274	2,200	2,940	2,710
220	244.8	7,514	2,170	2,910	2,690
230	254.8	7,754	2,150	2,880	2,660
240	264.8	7,994	2,130	2,850	2,630
250	274.8	8,234	2,110	2,810	2,600
260	284.8	8,474	2,090	2,770	2,580
270	294.8	8,714	2,070	2,740	2,560
280	304.8	8,954	2,050	2,700	2,530
290	314.8	9,194	2,030	2,660	2,510
300	324.8	9,434	2,010	2,630	2,490
310	334.8	9,674	2,000	2,600	2,470
320	344.8	9,914	1,980	2,560	2,450
330	354.8	10,154	1,960	2,530	2,430
340	364.8	10,394	1,950	2,500	2,410
350	374.8	10,634	1,930	2,480	2,390
360	384.8	10,874	1,920	2,450	2,370
370	394.8	11,114	1,910	2,420	2,360
380	404.8	11,354	1,890	2,400	2,340
390	414.8	11,594	1,880	2,370	2,320
400	424.8	11,834	1,870	2,350	2,310
410	434.8	12,074	1,850	2,320	2,290
420	444.8	12,314	1,840	2,300	2,280
430	454.8	12,554	1,830	2,280	2,260
440	464.8	12,794	1,820	2,260	2,250
450	474.8	13,034	1,810	2,240	2,230
460	484.8	13,274	1,800	2,220	2,220
470	494.8	13,514	1,780	2,200	2,210
480	504.8	13,754	1,770	2,180	2,190
490	514.8	13,994	1,760	2,160	2,180
500	524.8	14,234	1,750	2,140	2,170
510	534.8	14,474	1,740	2,120	2,160
520	544.8	14,714	1,730	2,100	2,150
530	554.8	14,954	1,730	2,090	2,130
540	564.8	15,194	1,720	2,070	2,120
550	574.8	15,434	1,710	2,050	2,110
560	584.8	15,674	1,700	2,040	2,100
570	594.8	15,914	1,690	2,020	2,090
580	604.8	16,154	1,680	2,010	2,080
590	614.8	16,394	1,670	1,990	2,070
600	624.8	16,634	1,670	1,980	2,060

■ 3) デッキ型枠時の許容スパン (MA 5 0 -1.2mm)

軽量コン(kN/m <sup>2</sup> ): 20			F=235 (N/mm <sup>2</sup> )		
コ/厚さ	溝コ/厚さ	総荷重	単純	2連続	3連続
(mm)	25.1	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	35.1	2,299	2,950	3,860	3,630
20	45.1	2,499	2,870	3,780	3,550
30	55.1	2,699	2,800	3,710	3,460
40	65.1	2,899	2,730	3,640	3,380
50	75.1	3,099	2,670	3,580	3,300
60	85.1	3,299	2,610	3,510	3,230
70	95.1	3,499	2,560	3,440	3,170
80	105.1	3,699	2,520	3,380	3,110
85	110.1	3,799	2,490	3,350	3,080
90	115.1	3,899	2,470	3,320	3,060
95	120.1	3,999	2,450	3,290	3,030
100	125.1	4,099	2,430	3,260	3,010
110	135.1	4,299	2,390	3,210	2,960
120	145.1	4,499	2,360	3,160	2,910
130	155.1	4,699	2,320	3,120	2,870
140	165.1	4,899	2,290	3,070	2,830
150	175.1	5,099	2,260	3,030	2,800
160	185.1	5,299	2,230	2,990	2,760
170	195.1	5,499	2,200	2,960	2,730
180	205.1	5,699	2,180	2,920	2,690
190	215.1	5,899	2,150	2,890	2,660
200	225.1	6,099	2,130	2,860	2,630
210	235.1	6,299	2,110	2,810	2,600
220	245.1	6,499	2,080	2,770	2,580
230	255.1	6,699	2,060	2,730	2,550
240	265.1	6,899	2,040	2,690	2,530
250	275.1	7,099	2,020	2,650	2,500
260	285.1	7,299	2,010	2,610	2,480
270	295.1	7,499	1,990	2,580	2,460
280	305.1	7,699	1,970	2,540	2,440
290	315.1	7,899	1,950	2,510	2,420
300	325.1	8,099	1,940	2,480	2,390
310	335.1	8,299	1,920	2,450	2,380
320	345.1	8,499	1,910	2,420	2,360
330	355.1	8,699	1,890	2,390	2,340
340	365.1	8,899	1,880	2,370	2,320
350	375.1	9,099	1,860	2,340	2,300
360	385.1	9,299	1,850	2,310	2,290
370	395.1	9,499	1,840	2,290	2,270
380	405.1	9,699	1,820	2,270	2,260
390	415.1	9,899	1,810	2,240	2,240
400	425.1	10,099	1,800	2,220	2,220
410	435.1	10,299	1,790	2,200	2,210
420	445.1	10,499	1,780	2,180	2,200
430	455.1	10,699	1,760	2,160	2,180
440	465.1	10,899	1,750	2,140	2,170
450	475.1	11,099	1,740	2,120	2,160
460	485.1	11,299	1,730	2,100	2,140
470	495.1	11,499	1,720	2,080	2,130
480	505.1	11,699	1,710	2,060	2,120
490	515.1	11,899	1,700	2,050	2,110
500	525.1	12,099	1,690	2,030	2,090
510	535.1	12,299	1,680	2,010	2,080
520	545.1	12,499	1,680	2,000	2,070
530	555.1	12,699	1,670	1,980	2,060
540	565.1	12,899	1,660	1,960	2,050
550	575.1	13,099	1,650	1,950	2,040
560	585.1	13,299	1,640	1,930	2,030
570	595.1	13,499	1,630</		