

■ 4) デッキ型枠時の許容スパン (U-II-1.0mm (A L N 1 0))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,455	3,510	4,240	4,140
20	53.0	2,655	3,420	4,080	4,060
30	63.0	2,855	3,340	3,930	3,980
40	73.0	3,055	3,260	3,800	3,920
50	83.0	3,255	3,190	3,680	3,860
60	93.0	3,455	3,130	3,580	3,800
70	103.0	3,655	3,070	3,480	3,750
80	113.0	3,855	3,020	3,380	3,700
90	123.0	4,055	2,970	3,300	3,650
100	133.0	4,255	2,920	3,220	3,600
110	143.0	4,455	2,880	3,150	3,520
120	153.0	4,655	2,830	3,080	3,440
130	163.0	4,855	2,790	3,020	3,370
140	173.0	5,055	2,760	2,950	3,300
150	183.0	5,255	2,720	2,900	3,240
160	193.0	5,455	2,690	2,840	3,180
170	203.0	5,655	2,650	2,790	3,120
180	213.0	5,855	2,620	2,750	3,070
190	223.0	6,055	2,600	2,700	3,020
200	233.0	6,255	2,570	2,660	2,970
210	243.0	6,455	2,540	2,610	2,920
220	253.0	6,655	2,510	2,570	2,880
230	263.0	6,855	2,490	2,540	2,840
240	273.0	7,055	2,460	2,500	2,800
250	283.0	7,255	2,430	2,470	2,760
260	293.0	7,455	2,400	2,430	2,720
270	303.0	7,655	2,360	2,400	2,680
280	313.0	7,855	2,330	2,370	2,650
290	323.0	8,055	2,300	2,340	2,620
300	333.0	8,255	2,280	2,310	2,580
310	343.0	8,455	2,250	2,280	2,550
320	353.0	8,655	2,220	2,260	2,520
330	363.0	8,855	2,200	2,230	2,500
340	373.0	9,055	2,170	2,210	2,470
350	383.0	9,255	2,150	2,180	2,440
360	393.0	9,455	2,130	2,160	2,410
370	403.0	9,655	2,100	2,140	2,390
380	413.0	9,855	2,080	2,110	2,360
390	423.0	10,055	2,060	2,090	2,340
400	433.0	10,255	2,040	2,070	2,320
410	443.0	10,455	2,020	2,050	2,300
420	453.0	10,655	2,000	2,030	2,270
430	463.0	10,855	1,980	2,010	2,250
440	473.0	11,055	1,970	2,000	2,230
450	483.0	11,255	1,950	1,980	2,210
460	493.0	11,455	1,930	1,960	2,190
470	503.0	11,655	1,920	1,940	2,170
480	513.0	11,855	1,900	1,930	2,160
490	523.0	12,055	1,880	1,910	2,140
500	533.0	12,255	1,870	1,900	2,120
510	543.0	12,455	1,850	1,880	2,100
520	553.0	12,655	1,840	1,870	2,090
530	563.0	12,855	1,820	1,850	2,070
540	573.0	13,055	1,810	1,840	2,050
550	583.0	13,255	1,800	1,820	2,040
560	593.0	13,455	1,780	1,810	2,020
570	603.0	13,655	1,770	1,800	2,010
580	613.0	13,855	1,760	1,780	1,990
590	623.0	14,055	1,740	1,770	1,980
600	633.0	14,255	1,730	1,760	1,970

■ 5) デッキ型枠時の許容スパン (U-II-1.2mm (A L N 1 2))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,478	3,680	4,580	4,310
20	53.0	2,678	3,610	4,500	4,230
30	63.0	2,878	3,530	4,420	4,160
40	73.0	3,078	3,450	4,340	4,090
50	83.0	3,278	3,380	4,220	4,020
60	93.0	3,478	3,310	4,090	3,960
70	103.0	3,678	3,250	3,980	3,910
80	113.0	3,878	3,190	3,880	3,860
90	123.0	4,078	3,140	3,780	3,810
100	133.0	4,278	3,090	3,690	3,760
110	143.0	4,478	3,040	3,610	3,720
120	153.0	4,678	3,000	3,530	3,680
130	163.0	4,878	2,960	3,450	3,640
140	173.0	5,078	2,920	3,390	3,600
150	183.0	5,278	2,880	3,320	3,560
160	193.0	5,478	2,850	3,260	3,520
170	203.0	5,678	2,810	3,200	3,480
180	213.0	5,878	2,780	3,150	3,440
190	223.0	6,078	2,750	3,090	3,400
200	233.0	6,278	2,720	3,040	3,360
210	243.0	6,478	2,690	3,000	3,330
220	253.0	6,678	2,660	2,950	3,290
230	263.0	6,878	2,640	2,910	3,250
240	273.0	7,078	2,610	2,870	3,210
250	283.0	7,278	2,590	2,830	3,160
260	293.0	7,478	2,560	2,790	3,120
270	303.0	7,678	2,540	2,750	3,080
280	313.0	7,878	2,520	2,720	3,040
290	323.0	8,078	2,500	2,680	3,000
300	333.0	8,278	2,480	2,650	2,960
310	343.0	8,478	2,460	2,620	2,930
320	353.0	8,678	2,440	2,590	2,890
330	363.0	8,878	2,420	2,560	2,860
340	373.0	9,078	2,400	2,530	2,830
350	383.0	9,278	2,390	2,500	2,800
360	393.0	9,478	2,370	2,480	2,770
370	403.0	9,678	2,350	2,450	2,740
380	413.0	9,878	2,340	2,430	2,710
390	423.0	10,078	2,320	2,400	2,690
400	433.0	10,278	2,310	2,380	2,660
410	443.0	10,478	2,290	2,360	2,630
420	453.0	10,678	2,280	2,330	2,610
430	463.0	10,878	2,260	2,310	2,590
440	473.0	11,078	2,250	2,290	2,560
450	483.0	11,278	2,230	2,270	2,540
460	493.0	11,478	2,220	2,250	2,520
470	503.0	11,678	2,200	2,230	2,490
480	513.0	11,878	2,180	2,210	2,470
490	523.0	12,078	2,160	2,190	2,450
500	533.0	12,278	2,140	2,180	2,430
510	543.0	12,478	2,120	2,160	2,410
520	553.0	12,678	2,110	2,140	2,390
530	563.0	12,878	2,090	2,120	2,380
540	573.0	13,078	2,070	2,110	2,360
550	583.0	13,278	2,060	2,090	2,340
560	593.0	13,478	2,040	2,080	2,320
570	603.0	13,678	2,030	2,060	2,300
580	613.0	13,878	2,010	2,050	2,290
590	623.0	14,078	2,000	2,030	2,270
600	633.0	14,278	1,990	2,020	2,260

■ 6) デッキ型枠時の許容スパン (U-II-1.6mm (A L N 1 6))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,526	3,920	4,880	4,590
20	53.0	2,726	3,840	4,790	4,510
30	63.0	2,926	3,780	4,710	4,430
40	73.0	3,126	3,710	4,630	4,350
50	83.0	3,326	3,660	4,560	4,290
60	93.0	3,526	3,600	4,490	4,230
70	103.0	3,726	3,540	4,430	4,170
80	113.0	3,926	3,480	4,370	4,110
90	123.0	4,126	3,420	4,320	4,060
100	133.0	4,326	3,370	4,270	4,010
110	143.0	4,526	3,320	4,220	3,970
120	153.0	4,726	3,270	4,170	3,930
130	163.0	4,926	3,230	4,130	3,890
140	173.0	5,126	3,180	4,090	3,850
150	183.0	5,326	3,140	4,050	3,810
160	193.0	5,526	3,100	4,010	3,780
170	203.0	5,726	3,070	3,980	3,740
180	213.0	5,926	3,030	3,920	3,710
190	223.0	6,126	3,000	3,860	3,680
200	233.0	6,326	2,970	3,800	3,650
210	243.0	6,526	2,940	3,740	3,620
220	253.0	6,726	2,910	3,680	3,590
230	263.0	6,926	2,880	3,630	3,560
240	273.0	7,126	2,850	3,580	3,530
250	283.0	7,326	2,830	3,530	3,490
260	293.0	7,526	2,800	3,480	3,460
270	303.0	7,726	2,780	3,430	3,430
280	313.0	7,926	2,750	3,390	3,400
290	323.0	8,126	2,730	3,350	3,370
300	333.0	8,326	2,710	3,310	3,350
310	343.0	8,526	2,690	3,270	3,320
320	353.0	8,726	2,670	3,230	3,300
330	363.0	8,926	2,650	3,190	3,270
340	373.0	9,126	2,630	3,160	3,250
350	383.0	9,326	2,610	3,120	3,220
360	393.0	9,526	2,590	3,090	3,200
370	403.0	9,726	2,570	3,060	3,180
380	413.0	9,926	2,550	3,030	3,160
390	423.0	10,126	2,540	3,000	3,140
400	433.0	10,326	2,520	2,970	3,120
410	443.0	10,526	2,500	2,940	3,100
420	453.0	10,726	2,490	2,910	3,080
430	463.0	10,926	2,470	2,890	3,060
440	473.0	11,126	2,460	2,860	3,040
450	483.0	11,326	2,440	2,830	3,020
460	493.0	11,526	2,430	2,810	3,000
470	503.0	11,726	2,420	2,790	2,990
480	513.0	11,926	2,400	2,760	2,970
490	523.0	12,126	2,390	2,740	2,950
500	533.0	12,326	2,380	2,720	2,940
510	543.0	12,526	2,360	2,700	2,920
520	553.0	12,726	2,350	2,670	2,910
530	563.0	12,926	2,340	2,650	2,890
540	573.0	13,126	2,330	2,630	2,880
550	583.0	13,326	2,310	2,610	2,860
560	593.0	13,526	2,300	2,590	2,850
570	603.0	13,726	2,290	2,570	2,830
580	613.0	13,926	2,280	2,560	2,820
590	623.0	14,126	2,270	2,540	2,810
600	633.0	14,326	2,260	2,520	2,790