

■ 1) デッキ型枠時の許容スパン (U-II-1.0mm (A L N 1 0))

普通コン(kN/m ²) ; 24			F=205 (N/mm)		
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,627	3,430	4,100	4,070
20	53.0	2,867	3,330	3,930	3,980
30	63.0	3,107	3,240	3,770	3,900
40	73.0	3,347	3,160	3,630	3,830
50	83.0	3,587	3,090	3,510	3,760
60	93.0	3,827	3,020	3,400	3,700
70	103.0	4,067	2,960	3,290	3,650
80	113.0	4,307	2,910	3,200	3,580
90	123.0	4,547	2,860	3,120	3,480
100	133.0	4,787	2,810	3,040	3,400
110	143.0	5,027	2,760	2,960	3,310
120	153.0	5,267	2,720	2,890	3,240
130	163.0	5,507	2,680	2,830	3,170
140	173.0	5,747	2,640	2,770	3,100
150	183.0	5,987	2,600	2,710	3,040
160	193.0	6,227	2,570	2,660	2,980
170	203.0	6,467	2,540	2,610	2,920
180	213.0	6,707	2,510	2,560	2,870
190	223.0	6,947	2,480	2,520	2,820
200	233.0	7,187	2,440	2,480	2,770
210	243.0	7,427	2,400	2,440	2,730
220	253.0	7,667	2,360	2,400	2,680
230	263.0	7,907	2,330	2,360	2,640
240	273.0	8,147	2,290	2,330	2,600
250	283.0	8,387	2,260	2,290	2,560
260	293.0	8,627	2,230	2,260	2,530
270	303.0	8,867	2,200	2,230	2,490
280	313.0	9,107	2,170	2,200	2,460
290	323.0	9,347	2,140	2,170	2,430
300	333.0	9,587	2,110	2,140	2,400
310	343.0	9,827	2,090	2,120	2,370
320	353.0	10,067	2,060	2,090	2,340
330	363.0	10,307	2,040	2,070	2,310
340	373.0	10,547	2,010	2,040	2,290
350	383.0	10,787	1,990	2,020	2,260
360	393.0	11,027	1,970	2,000	2,240
370	403.0	11,267	1,950	1,980	2,210
380	413.0	11,507	1,930	1,960	2,190
390	423.0	11,747	1,910	1,940	2,170
400	433.0	11,987	1,890	1,920	2,140
410	443.0	12,227	1,870	1,900	2,120
420	453.0	12,467	1,850	1,880	2,100
430	463.0	12,707	1,830	1,860	2,080
440	473.0	12,947	1,820	1,840	2,060
450	483.0	13,187	1,800	1,830	2,040
460	493.0	13,427	1,780	1,810	2,030
470	503.0	13,667	1,770	1,800	2,010
480	513.0	13,907	1,750	1,780	1,990
490	523.0	14,147	1,740	1,760	1,970
500	533.0	14,387	1,720	1,750	1,960
510	543.0	14,627	1,710	1,730	1,940
520	553.0	14,867	1,700	1,720	1,920
530	563.0	15,107	1,680	1,710	1,910
540	573.0	15,347	1,670	1,690	1,890
550	583.0	15,587	1,660	1,680	1,880
560	593.0	15,827	1,640	1,670	1,870
570	603.0	16,067	1,630	1,660	1,850
580	613.0	16,307	1,620	1,640	1,840
590	623.0	16,547	1,610	1,630	1,820
600	633.0	16,787	1,590	1,620	1,810

■ 2) デッキ型枠時の許容スパン (U-II-1.2mm (A L N 1 2))

普通コン(kN/m ²) ; 24			F=205 (N/mm)		
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,650	3,620	4,510	4,240
20	53.0	2,890	3,520	4,410	4,150
30	63.0	3,130	3,430	4,310	4,070
40	73.0	3,370	3,350	4,160	3,990
50	83.0	3,610	3,270	4,020	3,930
60	93.0	3,850	3,200	3,890	3,860
70	103.0	4,090	3,140	3,770	3,810
80	113.0	4,330	3,080	3,670	3,750
90	123.0	4,570	3,020	3,570	3,700
100	133.0	4,810	2,970	3,480	3,650
110	143.0	5,050	2,920	3,400	3,610
120	153.0	5,290	2,880	3,320	3,560
130	163.0	5,530	2,840	3,240	3,510
140	173.0	5,770	2,800	3,180	3,460
150	183.0	6,010	2,760	3,110	3,410
160	193.0	6,250	2,720	3,050	3,370
170	203.0	6,490	2,690	2,990	3,320
180	213.0	6,730	2,660	2,940	3,280
190	223.0	6,970	2,630	2,890	3,230
200	233.0	7,210	2,600	2,840	3,180
210	243.0	7,450	2,570	2,790	3,120
220	253.0	7,690	2,540	2,750	3,080
230	263.0	7,930	2,510	2,710	3,030
240	273.0	8,170	2,490	2,670	2,980
250	283.0	8,410	2,470	2,630	2,940
260	293.0	8,650	2,440	2,590	2,900
270	303.0	8,890	2,420	2,560	2,860
280	313.0	9,130	2,400	2,520	2,820
290	323.0	9,370	2,380	2,490	2,790
300	333.0	9,610	2,360	2,460	2,750
310	343.0	9,850	2,340	2,430	2,720
320	353.0	10,090	2,320	2,400	2,680
330	363.0	10,330	2,300	2,370	2,650
340	373.0	10,570	2,280	2,350	2,620
350	383.0	10,810	2,270	2,320	2,590
360	393.0	11,050	2,250	2,290	2,560
370	403.0	11,290	2,230	2,270	2,540
380	413.0	11,530	2,210	2,250	2,510
390	423.0	11,770	2,190	2,220	2,490
400	433.0	12,010	2,170	2,200	2,460
410	443.0	12,250	2,140	2,180	2,440
420	453.0	12,490	2,120	2,160	2,410
430	463.0	12,730	2,100	2,140	2,390
440	473.0	12,970	2,080	2,120	2,370
450	483.0	13,210	2,060	2,100	2,350
460	493.0	13,450	2,050	2,080	2,320
470	503.0	13,690	2,030	2,060	2,300
480	513.0	13,930	2,010	2,040	2,280
490	523.0	14,170	1,990	2,020	2,260
500	533.0	14,410	1,980	2,010	2,250
510	543.0	14,650	1,960	1,990	2,230
520	553.0	14,890	1,940	1,980	2,210
530	563.0	15,130	1,930	1,960	2,190
540	573.0	15,370	1,910	1,940	2,170
550	583.0	15,610	1,900	1,930	2,160
560	593.0	15,850	1,880	1,910	2,140
570	603.0	16,090	1,870	1,900	2,120
580	613.0	16,330	1,860	1,890	2,110
590	623.0	16,570	1,840	1,870	2,090
600	633.0	16,810	1,830	1,860	2,080

■ 3) デッキ型枠時の許容スパン (U-II-1.6mm (A L N 1 6))

普通コン(kN/m ²) ; 24			F=205 (N/mm)		
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,698	3,850	4,800	4,520
20	53.0	2,938	3,770	4,700	4,420
30	63.0	3,178	3,700	4,610	4,340
40	73.0	3,418	3,630	4,530	4,260
50	83.0	3,658	3,560	4,450	4,190
60	93.0	3,898	3,490	4,380	4,120
70	103.0	4,138	3,420	4,310	4,060
80	113.0	4,378	3,360	4,250	4,000
90	123.0	4,618	3,300	4,200	3,950
100	133.0	4,858	3,240	4,150	3,900
110	143.0	5,098	3,190	4,100	3,850
120	153.0	5,338	3,140	4,050	3,810
130	163.0	5,578	3,100	4,000	3,770
140	173.0	5,818	3,050	3,960	3,730
150	183.0	6,058	3,010	3,880	3,690
160	193.0	6,298	2,970	3,800	3,650
170	203.0	6,538	2,940	3,730	3,620
180	213.0	6,778	2,900	3,670	3,590
190	223.0	7,018	2,870	3,600	3,540
200	233.0	7,258	2,830	3,540	3,500
210	243.0	7,498	2,800	3,490	3,470
220	253.0	7,738	2,770	3,430	3,430
230	263.0	7,978	2,750	3,380	3,400
240	273.0	8,218	2,720	3,330	3,360
250	283.0	8,458	2,690	3,280	3,330
260	293.0	8,698	2,670	3,240	3,300
270	303.0	8,938	2,640	3,190	3,270
280	313.0	9,178	2,620	3,150	3,240
290	323.0	9,418	2,600	3,110	3,210
300	333.0	9,658	2,580	3,070	3,190
310	343.0	9,898	2,560	3,030	3,160
320	353.0	10,138	2,540	3,000	3,130
330	363.0	10,378	2,520	2,960	3,110
340	373.0	10,618	2,500	2,930	3,090
350	383.0	10,858	2,480	2,900	3,060
360	393.0	11,098	2,460	2,860	3,040
370	403.0	11,338	2,440	2,830	3,020
380	413.0	11,578	2,430	2,800	3,000
390	423.0	11,818	2,410	2,780	2,980
400	433.0	12,058	2,390	2,750	2,960
410	443.0	12,298	2,380	2,720	2,940
420	453.0	12,538	2,360	2,690	2,920
430	463.0	12,778	2,350	2,670	2,900
440	473.0	13,018	2,330	2,640	2,880
450	483.0	13,258	2,320	2,620	2,870
460	493.0	13,498	2,300	2,600	2,850
470	503.0	13,738	2,290	2,570	2,830
480	513.0	13,978	2,280	2,550	2,820
490	523.0	14,218	2,260	2,530	2,800
500	533.0	14,458	2,250	2,510	2,780
510	543.0	14,698	2,240	2,490	2,770
520	553.0	14,938	2,230	2,470	2,750
530	563.0	15,178	2,220	2,450	2,740
540	573.0	15,418	2,200	2,430	2,720
550	583.0	15,658	2,190	2,410	2,700
560	593.0	15,898	2,180	2,390	2,670
570	603.0	16,138	2,170	2,370	2,650
580	613.0	16,378	2,160	2,360	2,640
590	623.0	16,618	2,150	2,340	2,620
600	633.0	16,858	2,140	2,320	2,600