

■1) デッキ型枠時の許容スパン (UM-I-1.2mm (B L C 1 2))

普通コン(kN/m ²): 24			F=205 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	27	(N/m ²)	許容スパン	許容スパン	許容スパン
10	37.0	2,515	3,630	4,530	4,260
20	47.0	2,755	3,540	4,430	4,160
30	57.0	2,995	3,440	4,330	4,080
40	67.0	3,235	3,350	4,250	4,000
50	77.0	3,475	3,270	4,180	3,930
60	87.0	3,715	3,200	4,110	3,860
70	97.0	3,955	3,140	3,990	3,800
80	107.0	4,195	3,070	3,870	3,750
90	117.0	4,435	3,020	3,760	3,700
100	127.0	4,675	2,960	3,670	3,650
110	137.0	4,915	2,920	3,570	3,600
120	147.0	5,155	2,870	3,490	3,550
130	157.0	5,395	2,830	3,410	3,490
140	167.0	5,635	2,790	3,340	3,440
150	177.0	5,875	2,750	3,270	3,400
160	187.0	6,115	2,710	3,200	3,350
170	197.0	6,355	2,680	3,140	3,310
180	207.0	6,595	2,640	3,090	3,270
190	217.0	6,835	2,610	3,030	3,230
200	227.0	7,075	2,580	2,980	3,190
210	237.0	7,315	2,550	2,930	3,160
220	247.0	7,555	2,530	2,880	3,120
230	257.0	7,795	2,500	2,840	3,090
240	267.0	8,035	2,470	2,790	3,060
250	277.0	8,275	2,450	2,750	3,030
260	287.0	8,515	2,430	2,710	3,000
270	297.0	8,755	2,400	2,680	2,970
280	307.0	8,995	2,380	2,640	2,950
290	317.0	9,235	2,360	2,610	2,910
300	327.0	9,475	2,340	2,570	2,880
310	337.0	9,715	2,320	2,540	2,840
320	347.0	9,955	2,300	2,510	2,810
330	357.0	10,195	2,290	2,480	2,770
340	367.0	10,435	2,270	2,450	2,740
350	377.0	10,675	2,250	2,420	2,710
360	387.0	10,915	2,230	2,400	2,680
370	397.0	11,155	2,220	2,370	2,650
380	407.0	11,395	2,200	2,350	2,620
390	417.0	11,635	2,190	2,320	2,600
400	427.0	11,875	2,170	2,300	2,570
410	437.0	12,115	2,160	2,270	2,540
420	447.0	12,355	2,140	2,250	2,520
430	457.0	12,595	2,130	2,230	2,500
440	467.0	12,835	2,120	2,210	2,470
450	477.0	13,075	2,100	2,190	2,450
460	487.0	13,315	2,090	2,170	2,430
470	497.0	13,555	2,080	2,150	2,400
480	507.0	13,795	2,060	2,130	2,380
490	517.0	14,035	2,040	2,110	2,360
500	527.0	14,275	2,030	2,100	2,340
510	537.0	14,515	2,010	2,080	2,320
520	547.0	14,755	1,990	2,060	2,300
530	557.0	14,995	1,980	2,040	2,290
540	567.0	15,235	1,960	2,030	2,270
550	577.0	15,475	1,950	2,010	2,250
560	587.0	15,715	1,930	2,000	2,230
570	597.0	15,955	1,920	1,980	2,220
580	607.0	16,195	1,900	1,970	2,200
590	617.0	16,435	1,890	1,950	2,180
600	627.0	16,675	1,870	1,940	2,170

■2) デッキ型枠時の許容スパン (UM-I-1.6mm (B L C 1 6))

普通コン(kN/m ²): 24			F=205 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	27	(N/m ²)	許容スパン	許容スパン	許容スパン
10	37.0	2,564	3,870	4,820	4,540
20	47.0	2,804	3,780	4,710	4,440
30	57.0	3,044	3,710	4,620	4,350
40	67.0	3,284	3,640	4,530	4,260
50	77.0	3,524	3,570	4,450	4,190
60	87.0	3,764	3,490	4,380	4,120
70	97.0	4,004	3,420	4,310	4,060
80	107.0	4,244	3,350	4,250	4,000
90	117.0	4,484	3,290	4,190	3,940
100	127.0	4,724	3,230	4,140	3,890
110	137.0	4,964	3,180	4,070	3,840
120	147.0	5,204	3,130	3,970	3,800
130	157.0	5,444	3,080	3,880	3,760
140	167.0	5,684	3,040	3,800	3,720
150	177.0	5,924	3,000	3,720	3,680
160	187.0	6,164	2,960	3,650	3,640
170	197.0	6,404	2,920	3,580	3,610
180	207.0	6,644	2,880	3,520	3,570
190	217.0	6,884	2,850	3,450	3,520
200	227.0	7,124	2,820	3,390	3,480
210	237.0	7,364	2,790	3,340	3,450
220	247.0	7,604	2,760	3,290	3,410
230	257.0	7,844	2,730	3,230	3,370
240	267.0	8,084	2,700	3,190	3,340
250	277.0	8,324	2,680	3,140	3,310
260	287.0	8,564	2,650	3,100	3,280
270	297.0	8,804	2,630	3,050	3,250
280	307.0	9,044	2,600	3,010	3,220
290	317.0	9,284	2,580	2,970	3,190
300	327.0	9,524	2,560	2,940	3,160
310	337.0	9,764	2,540	2,900	3,140
320	347.0	10,004	2,520	2,860	3,110
330	357.0	10,244	2,500	2,830	3,090
340	367.0	10,484	2,480	2,800	3,060
350	377.0	10,724	2,460	2,770	3,040
360	387.0	10,964	2,440	2,740	3,020
370	397.0	11,204	2,420	2,710	3,000
380	407.0	11,444	2,410	2,680	2,970
390	417.0	11,684	2,390	2,650	2,950
400	427.0	11,924	2,370	2,620	2,930
410	437.0	12,164	2,360	2,600	2,900
420	447.0	12,404	2,340	2,570	2,880
430	457.0	12,644	2,330	2,550	2,850
440	467.0	12,884	2,310	2,520	2,820
450	477.0	13,124	2,300	2,500	2,800
460	487.0	13,364	2,280	2,480	2,770
470	497.0	13,604	2,270	2,460	2,750
480	507.0	13,844	2,260	2,430	2,720
490	517.0	14,084	2,240	2,410	2,700
500	527.0	14,324	2,230	2,390	2,680
510	537.0	14,564	2,220	2,370	2,650
520	547.0	14,804	2,210	2,350	2,630
530	557.0	15,044	2,200	2,330	2,610
540	567.0	15,284	2,180	2,320	2,590
550	577.0	15,524	2,170	2,300	2,570
560	587.0	15,764	2,160	2,280	2,550
570	597.0	16,004	2,150	2,260	2,530
580	607.0	16,244	2,140	2,250	2,510
590	617.0	16,484	2,130	2,230	2,490
600	627.0	16,724	2,120	2,210	2,480

■3) デッキ型枠時の許容スパン (UM-I-1.2mm (B L C 1 2))

軽量コン(kN/m ²): 20			F=205 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	27	(N/m ²)	許容スパン	許容スパン	許容スパン
10	37.0	2,367	3,690	4,600	4,330
20	47.0	2,567	3,620	4,500	4,240
30	57.0	2,767	3,530	4,420	4,160
40	67.0	2,967	3,450	4,340	4,090
50	77.0	3,167	3,380	4,270	4,020
60	87.0	3,367	3,310	4,210	3,960
70	97.0	3,567	3,250	4,150	3,900
80	107.0	3,767	3,190	4,080	3,850
90	117.0	3,967	3,130	3,980	3,800
100	127.0	4,167	3,080	3,880	3,750
110	137.0	4,367	3,030	3,790	3,710
120	147.0	4,567	2,990	3,710	3,670
130	157.0	4,767	2,950	3,630	3,630
140	167.0	4,967	2,910	3,560	3,590
150	177.0	5,167	2,870	3,490	3,550
160	187.0	5,367	2,830	3,420	3,500
170	197.0	5,567	2,800	3,360	3,460
180	207.0	5,767	2,760	3,300	3,420
190	217.0	5,967	2,730	3,240	3,380
200	227.0	6,167	2,700	3,190	3,340
210	237.0	6,367	2,670	3,140	3,310
220	247.0	6,567	2,650	3,090	3,270
230	257.0	6,767	2,620	3,050	3,240
240	267.0	6,967	2,600	3,000	3,210
250	277.0	7,167	2,570	2,960	3,180
260	287.0	7,367	2,550	2,920	3,150
270	297.0	7,567	2,520	2,880	3,120
280	307.0	7,767	2,500	2,840	3,090
290	317.0	7,967	2,480	2,810	3,070
300	327.0	8,167	2,460	2,770	3,040
310	337.0	8,367	2,440	2,740	3,020
320	347.0	8,567	2,420	2,710	2,990
330	357.0	8,767	2,400	2,680	2,970
340	367.0	8,967	2,390	2,650	2,950
350	377.0	9,167	2,370	2,620	2,930
360	387.0	9,367	2,350	2,590	2,890
370	397.0	9,567	2,330	2,560	2,860
380	407.0	9,767	2,320	2,530	2,830
390	417.0	9,967	2,300	2,510	2,810
400	427.0	10,167	2,290	2,480	2,780
410	437.0	10,367	2,270	2,460	2,750
420	447.0	10,567	2,260	2,440	2,720
430	457.0	10,767	2,240	2,410	2,700
440	467.0	10,967	2,230	2,390	2,670
450	477.0	11,167	2,220	2,370	2,650
460	487.0	11,367	2,200	2,350	2,630
470	497.0	11,567	2,190	2,330	2,600
480	507.0	11,767	2,180	2,310	2,580
490	517.0	11,967	2,170	2,290	2,560
500	527.0	12,167	2,150	2,270	2,540
510	537.0	12,367	2,140	2,250	2,520
520	547.0	12,567	2,130	2,230	2,500
530	557.0	12,767	2,120	2,220	2,480
540	567.0	12,967	2,110	2,200	2,460
550	577.0	13,167	2,100	2,180	2,440
560	587.0	13,367	2,090	2,170	2,420
570	597.0	13,567	2,080	2,150	2,400
580	607.0	13,767	2,060	2,130	2,390
590	617.0	13,967	2,050	2,120	2,370
600	627.0	14,167	2,030	2,100	2,350

■4) デッキ型枠時の許容スパン (UM-I-1.6mm (B L C 1 6))

軽量コン(kN/m ²): 20			F=205 (N/mm ²)</		
------------------------------	--	--	------------------------------	--	--