

■ 4) デッキ型枠時の許容スパン (UM-II-1.0mm (BLD10))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,455	3,500	4,230	4,130
20	53.0	2,655	3,410	4,060	4,050
30	63.0	2,855	3,330	3,920	3,980
40	73.0	3,055	3,250	3,790	3,910
50	83.0	3,255	3,190	3,670	3,850
60	93.0	3,455	3,120	3,560	3,790
70	103.0	3,655	3,060	3,460	3,740
80	113.0	3,855	3,010	3,370	3,690
90	123.0	4,055	2,960	3,290	3,640
100	133.0	4,255	2,910	3,210	3,590
110	143.0	4,455	2,870	3,140	3,510
120	153.0	4,655	2,830	3,070	3,430
130	163.0	4,855	2,790	3,000	3,360
140	173.0	5,055	2,750	2,940	3,290
150	183.0	5,255	2,710	2,890	3,230
160	193.0	5,455	2,680	2,830	3,170
170	203.0	5,655	2,650	2,780	3,110
180	213.0	5,855	2,620	2,730	3,060
190	223.0	6,055	2,590	2,690	3,010
200	233.0	6,255	2,560	2,650	2,960
210	243.0	6,455	2,530	2,600	2,910
220	253.0	6,655	2,510	2,560	2,870
230	263.0	6,855	2,480	2,530	2,830
240	273.0	7,055	2,460	2,490	2,790
250	283.0	7,255	2,430	2,460	2,750
260	293.0	7,455	2,400	2,420	2,710
270	303.0	7,655	2,360	2,390	2,670
280	313.0	7,855	2,330	2,360	2,640
290	323.0	8,055	2,300	2,330	2,610
300	333.0	8,255	2,280	2,300	2,570
310	343.0	8,455	2,250	2,280	2,540
320	353.0	8,655	2,220	2,250	2,510
330	363.0	8,855	2,200	2,220	2,490
340	373.0	9,055	2,170	2,200	2,460
350	383.0	9,255	2,150	2,170	2,430
360	393.0	9,455	2,130	2,150	2,410
370	403.0	9,655	2,100	2,130	2,380
380	413.0	9,855	2,080	2,110	2,360
390	423.0	10,055	2,060	2,090	2,330
400	433.0	10,255	2,040	2,070	2,310
410	443.0	10,455	2,020	2,050	2,290
420	453.0	10,655	2,000	2,030	2,270
430	463.0	10,855	1,980	2,010	2,240
440	473.0	11,055	1,970	1,990	2,220
450	483.0	11,255	1,950	1,970	2,200
460	493.0	11,455	1,930	1,950	2,190
470	503.0	11,655	1,920	1,940	2,170
480	513.0	11,855	1,900	1,920	2,150
490	523.0	12,055	1,880	1,900	2,130
500	533.0	12,255	1,870	1,890	2,110
510	543.0	12,455	1,850	1,870	2,100
520	553.0	12,655	1,840	1,860	2,080
530	563.0	12,855	1,820	1,840	2,060
540	573.0	13,055	1,810	1,830	2,050
550	583.0	13,255	1,800	1,820	2,030
560	593.0	13,455	1,780	1,800	2,020
570	603.0	13,655	1,770	1,790	2,000
580	613.0	13,855	1,760	1,780	1,990
590	623.0	14,055	1,740	1,760	1,970
600	633.0	14,255	1,730	1,750	1,960

■ 5) デッキ型枠時の許容スパン (UM-II-1.2mm (BLD12))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,479	3,670	4,580	4,310
20	53.0	2,679	3,600	4,490	4,220
30	63.0	2,879	3,520	4,410	4,150
40	73.0	3,079	3,440	4,340	4,080
50	83.0	3,279	3,370	4,200	4,020
60	93.0	3,479	3,300	4,080	3,960
70	103.0	3,679	3,240	3,970	3,900
80	113.0	3,879	3,190	3,860	3,850
90	123.0	4,079	3,130	3,770	3,800
100	133.0	4,279	3,080	3,680	3,760
110	143.0	4,479	3,040	3,600	3,710
120	153.0	4,679	2,990	3,520	3,670
130	163.0	4,879	2,950	3,440	3,640
140	173.0	5,079	2,910	3,380	3,600
150	183.0	5,279	2,870	3,310	3,550
160	193.0	5,479	2,840	3,250	3,510
170	203.0	5,679	2,810	3,190	3,470
180	213.0	5,879	2,770	3,140	3,430
190	223.0	6,079	2,740	3,090	3,390
200	233.0	6,279	2,710	3,040	3,350
210	243.0	6,479	2,680	2,990	3,320
220	253.0	6,679	2,660	2,940	3,290
230	263.0	6,879	2,630	2,900	3,240
240	273.0	7,079	2,610	2,860	3,200
250	283.0	7,279	2,580	2,820	3,150
260	293.0	7,479	2,560	2,780	3,110
270	303.0	7,679	2,540	2,740	3,070
280	313.0	7,879	2,520	2,710	3,030
290	323.0	8,079	2,490	2,680	2,990
300	333.0	8,279	2,470	2,640	2,960
310	343.0	8,479	2,450	2,610	2,920
320	353.0	8,679	2,440	2,580	2,890
330	363.0	8,879	2,420	2,550	2,850
340	373.0	9,079	2,400	2,520	2,820
350	383.0	9,279	2,380	2,500	2,790
360	393.0	9,479	2,360	2,470	2,760
370	403.0	9,679	2,350	2,440	2,730
380	413.0	9,879	2,330	2,420	2,710
390	423.0	10,079	2,320	2,400	2,680
400	433.0	10,279	2,300	2,370	2,650
410	443.0	10,479	2,290	2,350	2,630
420	453.0	10,679	2,270	2,330	2,600
430	463.0	10,879	2,260	2,310	2,580
440	473.0	11,079	2,240	2,280	2,550
450	483.0	11,279	2,230	2,260	2,530
460	493.0	11,479	2,220	2,240	2,510
470	503.0	11,679	2,200	2,220	2,490
480	513.0	11,879	2,180	2,210	2,470
490	523.0	12,079	2,160	2,190	2,450
500	533.0	12,279	2,140	2,170	2,430
510	543.0	12,479	2,120	2,150	2,410
520	553.0	12,679	2,110	2,130	2,390
530	563.0	12,879	2,090	2,120	2,370
540	573.0	13,079	2,070	2,100	2,350
550	583.0	13,279	2,060	2,090	2,330
560	593.0	13,479	2,040	2,070	2,320
570	603.0	13,679	2,030	2,060	2,300
580	613.0	13,879	2,010	2,040	2,280
590	623.0	14,079	2,000	2,030	2,270
600	633.0	14,279	1,990	2,010	2,250

■ 6) デッキ型枠時の許容スパン (UM-II-1.6mm (BLD16))

軽量コン(kN/m ²) ; 20		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m ²)	許容スパン	許容スパン	許容スパン
10	43.0	2,526	3,920	4,880	4,590
20	53.0	2,726	3,840	4,790	4,510
30	63.0	2,926	3,780	4,710	4,430
40	73.0	3,126	3,710	4,630	4,350
50	83.0	3,326	3,660	4,560	4,290
60	93.0	3,526	3,600	4,490	4,230
70	103.0	3,726	3,540	4,430	4,170
80	113.0	3,926	3,480	4,370	4,110
90	123.0	4,126	3,420	4,320	4,060
100	133.0	4,326	3,370	4,270	4,010
110	143.0	4,526	3,320	4,220	3,970
120	153.0	4,726	3,270	4,170	3,930
130	163.0	4,926	3,230	4,130	3,890
140	173.0	5,126	3,180	4,090	3,850
150	183.0	5,326	3,140	4,050	3,810
160	193.0	5,526	3,100	4,010	3,780
170	203.0	5,726	3,070	3,980	3,740
180	213.0	5,926	3,030	3,920	3,710
190	223.0	6,126	3,000	3,860	3,680
200	233.0	6,326	2,970	3,800	3,650
210	243.0	6,526	2,940	3,740	3,620
220	253.0	6,726	2,910	3,680	3,590
230	263.0	6,926	2,880	3,630	3,560
240	273.0	7,126	2,850	3,580	3,530
250	283.0	7,326	2,830	3,530	3,490
260	293.0	7,526	2,800	3,480	3,460
270	303.0	7,726	2,780	3,430	3,430
280	313.0	7,926	2,750	3,390	3,400
290	323.0	8,126	2,730	3,350	3,370
300	333.0	8,326	2,710	3,310	3,350
310	343.0	8,526	2,690	3,270	3,320
320	353.0	8,726	2,670	3,230	3,300
330	363.0	8,926	2,650	3,190	3,270
340	373.0	9,126	2,630	3,160	3,250
350	383.0	9,326	2,610	3,120	3,220
360	393.0	9,526	2,590	3,090	3,200
370	403.0	9,726	2,570	3,060	3,180
380	413.0	9,926	2,550	3,030	3,160
390	423.0	10,126	2,540	3,000	3,140
400	433.0	10,326	2,520	2,970	3,120
410	443.0	10,526	2,500	2,940	3,100
420	453.0	10,726	2,490	2,910	3,080
430	463.0	10,926	2,470	2,890	3,060
440	473.0	11,126	2,460	2,860	3,040
450	483.0	11,326	2,440	2,830	3,020
460	493.0	11,526	2,430	2,810	3,000
470	503.0	11,726	2,420	2,790	2,990
480	513.0	11,926	2,400	2,760	2,970
490	523.0	12,126	2,390	2,740	2,950
500	533.0	12,326	2,380	2,720	2,940
510	543.0	12,526	2,360	2,700	2,920
520	553.0	12,726	2,350	2,670	2,910
530	563.0	12,926	2,340	2,650	2,890
540	573.0	13,126	2,330	2,630	2,880
550	583.0	13,326	2,310	2,610	2,860
560	593.0	13,526	2,300	2,590	2,850
570	603.0	13,726	2,290	2,570	2,830
580	613.0	13,926	2,280	2,560	2,820
590	623.0	14,126	2,270	2,540	2,810
600	633.0	14,326	2,260	2,520	2,790