

■ 1) デッキ型枠時の許容スパン (UM-II -1.0mm (BLD 1 0))

普通コン(kN/m <sup>2</sup> ) ; 24		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m)	許容スパン	許容スパン	許容スパン
10	43.0	2,627	3,420	4,090	4,060
20	53.0	2,867	3,320	3,910	3,970
30	63.0	3,107	3,240	3,760	3,890
40	73.0	3,347	3,160	3,620	3,820
50	83.0	3,587	3,080	3,500	3,760
60	93.0	3,827	3,020	3,380	3,700
70	103.0	4,067	2,960	3,280	3,640
80	113.0	4,307	2,900	3,190	3,570
90	123.0	4,547	2,850	3,100	3,470
100	133.0	4,787	2,800	3,030	3,380
110	143.0	5,027	2,760	2,950	3,300
120	153.0	5,267	2,710	2,880	3,220
130	163.0	5,507	2,670	2,820	3,150
140	173.0	5,747	2,630	2,760	3,090
150	183.0	5,987	2,600	2,700	3,020
160	193.0	6,227	2,560	2,650	2,970
170	203.0	6,467	2,530	2,600	2,910
180	213.0	6,707	2,500	2,560	2,860
190	223.0	6,947	2,470	2,510	2,810
200	233.0	7,187	2,440	2,470	2,760
210	243.0	7,427	2,400	2,430	2,710
220	253.0	7,667	2,360	2,390	2,670
230	263.0	7,907	2,330	2,350	2,630
240	273.0	8,147	2,290	2,320	2,590
250	283.0	8,387	2,260	2,280	2,550
260	293.0	8,627	2,230	2,250	2,520
270	303.0	8,867	2,200	2,220	2,480
280	313.0	9,107	2,170	2,190	2,450
290	323.0	9,347	2,140	2,160	2,420
300	333.0	9,587	2,110	2,140	2,390
310	343.0	9,827	2,090	2,110	2,360
320	353.0	10,067	2,060	2,080	2,330
330	363.0	10,307	2,040	2,060	2,300
340	373.0	10,547	2,010	2,040	2,280
350	383.0	10,787	1,990	2,010	2,250
360	393.0	11,027	1,970	1,990	2,230
370	403.0	11,267	1,950	1,970	2,200
380	413.0	11,507	1,930	1,950	2,180
390	423.0	11,747	1,910	1,930	2,160
400	433.0	11,987	1,890	1,910	2,140
410	443.0	12,227	1,870	1,890	2,110
420	453.0	12,467	1,850	1,870	2,090
430	463.0	12,707	1,830	1,850	2,070
440	473.0	12,947	1,820	1,840	2,060
450	483.0	13,187	1,800	1,820	2,040
460	493.0	13,427	1,780	1,800	2,020
470	503.0	13,667	1,770	1,790	2,000
480	513.0	13,907	1,750	1,770	1,980
490	523.0	14,147	1,740	1,760	1,970
500	533.0	14,387	1,720	1,740	1,950
510	543.0	14,627	1,710	1,730	1,930
520	553.0	14,867	1,700	1,710	1,920
530	563.0	15,107	1,680	1,700	1,900
540	573.0	15,347	1,670	1,690	1,890
550	583.0	15,587	1,660	1,670	1,870
560	593.0	15,827	1,640	1,660	1,860
570	603.0	16,067	1,630	1,650	1,840
580	613.0	16,307	1,620	1,640	1,830
590	623.0	16,547	1,610	1,620	1,820
600	633.0	16,787	1,590	1,610	1,800

■ 2) デッキ型枠時の許容スパン (UM-II -1.2mm (BLD 1 2))

普通コン(kN/m <sup>2</sup> ) ; 24		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m)	許容スパン	許容スパン	許容スパン
10	43.0	2,651	3,610	4,500	4,240
20	53.0	2,891	3,520	4,410	4,140
30	63.0	3,131	3,420	4,300	4,060
40	73.0	3,371	3,340	4,140	3,990
50	83.0	3,611	3,260	4,000	3,920
60	93.0	3,851	3,190	3,880	3,860
70	103.0	4,091	3,130	3,760	3,800
80	113.0	4,331	3,070	3,660	3,750
90	123.0	4,571	3,020	3,560	3,700
100	133.0	4,811	2,970	3,470	3,650
110	143.0	5,051	2,920	3,390	3,600
120	153.0	5,291	2,870	3,310	3,550
130	163.0	5,531	2,830	3,230	3,500
140	173.0	5,771	2,790	3,170	3,450
150	183.0	6,011	2,750	3,100	3,400
160	193.0	6,251	2,720	3,040	3,360
170	203.0	6,491	2,680	2,990	3,320
180	213.0	6,731	2,650	2,930	3,280
190	223.0	6,971	2,620	2,880	3,220
200	233.0	7,211	2,590	2,830	3,170
210	243.0	7,451	2,560	2,790	3,120
220	253.0	7,691	2,540	2,740	3,070
230	263.0	7,931	2,510	2,700	3,020
240	273.0	8,171	2,480	2,660	2,980
250	283.0	8,411	2,460	2,620	2,930
260	293.0	8,651	2,440	2,590	2,890
270	303.0	8,891	2,420	2,550	2,850
280	313.0	9,131	2,390	2,520	2,810
290	323.0	9,371	2,370	2,480	2,780
300	333.0	9,611	2,350	2,450	2,740
310	343.0	9,851	2,330	2,420	2,710
320	353.0	10,091	2,320	2,390	2,680
330	363.0	10,331	2,300	2,370	2,650
340	373.0	10,571	2,280	2,340	2,620
350	383.0	10,811	2,260	2,310	2,590
360	393.0	11,051	2,250	2,290	2,560
370	403.0	11,291	2,230	2,260	2,530
380	413.0	11,531	2,210	2,240	2,500
390	423.0	11,771	2,190	2,220	2,480
400	433.0	12,011	2,170	2,190	2,450
410	443.0	12,251	2,140	2,170	2,430
420	453.0	12,491	2,120	2,150	2,410
430	463.0	12,731	2,100	2,130	2,380
440	473.0	12,971	2,080	2,110	2,360
450	483.0	13,211	2,060	2,090	2,340
460	493.0	13,451	2,050	2,070	2,320
470	503.0	13,691	2,030	2,050	2,300
480	513.0	13,931	2,010	2,040	2,280
490	523.0	14,171	1,990	2,020	2,260
500	533.0	14,411	1,980	2,000	2,240
510	543.0	14,651	1,960	1,990	2,220
520	553.0	14,891	1,940	1,970	2,200
530	563.0	15,131	1,930	1,950	2,190
540	573.0	15,371	1,910	1,940	2,170
550	583.0	15,611	1,900	1,920	2,150
560	593.0	15,851	1,880	1,910	2,130
570	603.0	16,091	1,870	1,890	2,120
580	613.0	16,331	1,860	1,880	2,100
590	623.0	16,571	1,840	1,870	2,090
600	633.0	16,811	1,830	1,850	2,070

■ 3) デッキ型枠時の許容スパン (UM-II -1.6mm (BLD 1 6))

普通コン(kN/m <sup>2</sup> ) ; 24		F=205 (N/mm)			
コソ厚さ	溝コソ厚さ	総荷重	単純	2連続	3連続
(mm)	33	(N/m)	許容スパン	許容スパン	許容スパン
10	43.0	2,698	3,850	4,800	4,520
20	53.0	2,938	3,770	4,700	4,420
30	63.0	3,178	3,700	4,610	4,340
40	73.0	3,418	3,630	4,530	4,260
50	83.0	3,658	3,560	4,450	4,190
60	93.0	3,898	3,490	4,380	4,120
70	103.0	4,138	3,420	4,310	4,060
80	113.0	4,378	3,360	4,250	4,000
90	123.0	4,618	3,300	4,200	3,950
100	133.0	4,858	3,240	4,150	3,900
110	143.0	5,098	3,190	4,100	3,850
120	153.0	5,338	3,140	4,050	3,810
130	163.0	5,578	3,100	4,000	3,770
140	173.0	5,818	3,050	3,960	3,730
150	183.0	6,058	3,010	3,880	3,690
160	193.0	6,298	2,970	3,800	3,650
170	203.0	6,538	2,940	3,730	3,620
180	213.0	6,778	2,900	3,670	3,590
190	223.0	7,018	2,870	3,600	3,540
200	233.0	7,258	2,830	3,540	3,500
210	243.0	7,498	2,800	3,490	3,470
220	253.0	7,738	2,770	3,430	3,430
230	263.0	7,978	2,750	3,380	3,400
240	273.0	8,218	2,720	3,330	3,360
250	283.0	8,458	2,690	3,280	3,330
260	293.0	8,698	2,670	3,240	3,300
270	303.0	8,938	2,640	3,190	3,270
280	313.0	9,178	2,620	3,150	3,240
290	323.0	9,418	2,600	3,110	3,210
300	333.0	9,658	2,580	3,070	3,190
310	343.0	9,898	2,560	3,030	3,160
320	353.0	10,138	2,540	3,000	3,130
330	363.0	10,378	2,520	2,960	3,110
340	373.0	10,618	2,500	2,930	3,090
350	383.0	10,858	2,480	2,900	3,060
360	393.0	11,098	2,460	2,860	3,040
370	403.0	11,338	2,440	2,830	3,020
380	413.0	11,578	2,430	2,800	3,000
390	423.0	11,818	2,410	2,780	2,980
400	433.0	12,058	2,390	2,750	2,960
410	443.0	12,298	2,380	2,720	2,940
420	453.0	12,538	2,360	2,690	2,920
430	463.0	12,778	2,350	2,670	2,900
440	473.0	13,018	2,330	2,640	2,880
450	483.0	13,258	2,320	2,620	2,870
460	493.0	13,498	2,300	2,600	2,850
470	503.0	13,738	2,290	2,570	2,830
480	513.0	13,978	2,280	2,550	2,820
490	523.0	14,218	2,260	2,530	2,800
500	533.0	14,458	2,250	2,510	2,780
510	543.0	14,698	2,240	2,490	2,770
520	553.0	14,938	2,230	2,470	2,750
530	563.0	15,178	2,220	2,450	2,740
540	573.0	15,418	2,200	2,430	2,720
550	583.0	15,658	2,190	2,410	2,700
560	593.0	15,898	2,180	2,390	2,670
570	603.0	16,138	2,170	2,370	2,650
580	613.0	16,378	2,160	2,360	2,640
590	623.0	16,618	2,150	2,340	2,620
600	633.0	16,858	2,140	2,320	2,600