

■ 6) デッキ型枠時の許容スパン (V50-1.2mm (ALB12))

軽量コン(kN/m <sup>2</sup> ) ; 20			F=205 (N/mm <sup>2</sup> )		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	22.0	2,043	2,780	3,690	3,440
20	32.0	2,243	2,690	3,580	3,330
30	42.0	2,443	2,620	3,430	3,240
40	52.0	2,643	2,550	3,300	3,150
50	62.0	2,843	2,490	3,180	3,080
60	72.0	3,043	2,430	3,070	3,010
70	82.0	3,243	2,380	2,980	2,940
80	92.0	3,443	2,330	2,890	2,890
90	102.0	3,643	2,290	2,810	2,830
100	112.0	3,843	2,250	2,740	2,780
110	122.0	4,043	2,210	2,670	2,740
120	132.0	4,243	2,180	2,600	2,690
130	142.0	4,443	2,140	2,540	2,650
140	152.0	4,643	2,110	2,490	2,610
150	162.0	4,843	2,080	2,440	2,580
160	172.0	5,043	2,060	2,390	2,540
170	182.0	5,243	2,030	2,340	2,510
180	192.0	5,443	2,000	2,300	2,480
190	202.0	5,643	1,980	2,260	2,450
200	212.0	5,843	1,960	2,220	2,420
210	222.0	6,043	1,930	2,180	2,390
220	232.0	6,243	1,910	2,150	2,370
230	242.0	6,443	1,890	2,110	2,340
240	252.0	6,643	1,870	2,080	2,320
250	262.0	6,843	1,860	2,050	2,290
260	272.0	7,043	1,840	2,020	2,260
270	282.0	7,243	1,820	1,990	2,230
280	292.0	7,443	1,800	1,960	2,200
290	302.0	7,643	1,790	1,940	2,170
300	312.0	7,843	1,770	1,910	2,140
310	322.0	8,043	1,760	1,890	2,110
320	332.0	8,243	1,740	1,870	2,090
330	342.0	8,443	1,730	1,840	2,060
340	352.0	8,643	1,720	1,820	2,040
350	362.0	8,843	1,700	1,800	2,010
360	372.0	9,043	1,690	1,780	1,990
370	382.0	9,243	1,680	1,760	1,970
380	392.0	9,443	1,660	1,740	1,950
390	402.0	9,643	1,640	1,730	1,930
400	412.0	9,843	1,630	1,710	1,910
410	422.0	10,043	1,610	1,690	1,890
420	432.0	10,243	1,600	1,670	1,870
430	442.0	10,443	1,580	1,660	1,850
440	452.0	10,643	1,570	1,640	1,840
450	462.0	10,843	1,550	1,630	1,820
460	472.0	11,043	1,540	1,610	1,800
470	482.0	11,243	1,520	1,600	1,790
480	492.0	11,443	1,510	1,580	1,770
490	502.0	11,643	1,500	1,570	1,760
500	512.0	11,843	1,480	1,560	1,740
510	522.0	12,043	1,470	1,540	1,730
520	532.0	12,243	1,460	1,530	1,710
530	542.0	12,443	1,450	1,520	1,700
540	552.0	12,643	1,440	1,510	1,680
550	562.0	12,843	1,420	1,490	1,670
560	572.0	13,043	1,410	1,480	1,660
570	582.0	13,243	1,400	1,470	1,650
580	592.0	13,443	1,390	1,460	1,630
590	602.0	13,643	1,380	1,450	1,620
600	612.0	13,843	1,370	1,440	1,610

■ 8) デッキ型枠時の許容スパン (V50-1.6mm (ALB16))

軽量コン(kN/m <sup>2</sup> ) ; 20			F=205 (N/mm <sup>2</sup> )		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	22.0	2,085	3,010	3,920	3,690
20	32.0	2,285	2,920	3,830	3,610
30	42.0	2,485	2,840	3,750	3,510
40	52.0	2,685	2,770	3,680	3,420
50	62.0	2,885	2,700	3,600	3,340
60	72.0	3,085	2,640	3,480	3,270
70	82.0	3,285	2,590	3,380	3,200
80	92.0	3,485	2,540	3,280	3,140
90	102.0	3,685	2,490	3,190	3,080
100	112.0	3,885	2,450	3,100	3,020
110	122.0	4,085	2,410	3,030	2,970
120	132.0	4,285	2,370	2,960	2,930
130	142.0	4,485	2,330	2,890	2,880
140	152.0	4,685	2,300	2,830	2,840
150	162.0	4,885	2,270	2,770	2,800
160	172.0	5,085	2,240	2,710	2,760
170	182.0	5,285	2,210	2,660	2,730
180	192.0	5,485	2,180	2,610	2,700
190	202.0	5,685	2,150	2,570	2,660
200	212.0	5,885	2,130	2,520	2,630
210	222.0	6,085	2,110	2,480	2,600
220	232.0	6,285	2,080	2,440	2,580
230	242.0	6,485	2,060	2,400	2,550
240	252.0	6,685	2,040	2,370	2,520
250	262.0	6,885	2,020	2,330	2,500
260	272.0	7,085	2,000	2,300	2,470
270	282.0	7,285	1,980	2,270	2,450
280	292.0	7,485	1,960	2,230	2,430
290	302.0	7,685	1,950	2,210	2,410
300	312.0	7,885	1,930	2,180	2,390
310	322.0	8,085	1,910	2,150	2,370
320	332.0	8,285	1,900	2,120	2,350
330	342.0	8,485	1,880	2,100	2,330
340	352.0	8,685	1,870	2,070	2,310
350	362.0	8,885	1,860	2,050	2,290
360	372.0	9,085	1,840	2,030	2,270
370	382.0	9,285	1,830	2,010	2,240
380	392.0	9,485	1,820	1,980	2,220
390	402.0	9,685	1,800	1,960	2,200
400	412.0	9,885	1,790	1,940	2,170
410	422.0	10,085	1,780	1,920	2,150
420	432.0	10,285	1,770	1,910	2,130
430	442.0	10,485	1,760	1,890	2,110
440	452.0	10,685	1,740	1,870	2,090
450	462.0	10,885	1,730	1,850	2,070
460	472.0	11,085	1,720	1,840	2,050
470	482.0	11,285	1,710	1,820	2,030
480	492.0	11,485	1,700	1,800	2,020
490	502.0	11,685	1,690	1,790	2,000
500	512.0	11,885	1,680	1,770	1,980
510	522.0	12,085	1,670	1,760	1,970
520	532.0	12,285	1,660	1,740	1,950
530	542.0	12,485	1,660	1,730	1,930
540	552.0	12,685	1,650	1,720	1,920
550	562.0	12,885	1,640	1,700	1,900
560	572.0	13,085	1,630	1,690	1,890
570	582.0	13,285	1,620	1,680	1,870
580	592.0	13,485	1,610	1,660	1,860
590	602.0	13,685	1,600	1,650	1,850
600	612.0	13,885	1,590	1,640	1,830