

■ 5) デッキ型枠時の許容スパン (V50-1.2mm (ALB12))

軽量コン(kN/m²) ; 20 F=235 (N/mm²)

コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,043	2,780	3,690	3,440
20	32.0	2,243	2,690	3,610	3,330
30	42.0	2,443	2,620	3,510	3,240
40	52.0	2,643	2,550	3,420	3,150
50	62.0	2,843	2,490	3,340	3,080
60	72.0	3,043	2,430	3,260	3,010
70	82.0	3,243	2,380	3,190	2,940
80	92.0	3,443	2,330	3,090	2,890
90	102.0	3,643	2,290	3,010	2,830
100	112.0	3,843	2,250	2,930	2,780
110	122.0	4,043	2,210	2,860	2,740
120	132.0	4,243	2,180	2,790	2,690
130	142.0	4,443	2,140	2,720	2,650
140	152.0	4,643	2,110	2,660	2,610
150	162.0	4,843	2,080	2,610	2,580
160	172.0	5,043	2,060	2,560	2,540
170	182.0	5,243	2,030	2,510	2,510
180	192.0	5,443	2,000	2,460	2,480
190	202.0	5,643	1,980	2,420	2,450
200	212.0	5,843	1,960	2,370	2,420
210	222.0	6,043	1,930	2,330	2,390
220	232.0	6,243	1,910	2,300	2,370
230	242.0	6,443	1,890	2,260	2,340
240	252.0	6,643	1,870	2,230	2,320
250	262.0	6,843	1,860	2,190	2,290
260	272.0	7,043	1,840	2,160	2,270
270	282.0	7,243	1,820	2,130	2,250
280	292.0	7,443	1,800	2,100	2,230
290	302.0	7,643	1,790	2,080	2,210
300	312.0	7,843	1,770	2,050	2,190
310	322.0	8,043	1,760	2,020	2,170
320	332.0	8,243	1,740	2,000	2,160
330	342.0	8,443	1,730	1,970	2,140
340	352.0	8,643	1,720	1,950	2,120
350	362.0	8,843	1,700	1,930	2,110
360	372.0	9,043	1,690	1,910	2,090
370	382.0	9,243	1,680	1,890	2,080
380	392.0	9,443	1,670	1,870	2,060
390	402.0	9,643	1,650	1,850	2,050
400	412.0	9,843	1,640	1,830	2,030
410	422.0	10,043	1,630	1,810	2,020
420	432.0	10,243	1,620	1,790	2,000
430	442.0	10,443	1,610	1,770	1,990
440	452.0	10,643	1,600	1,760	1,970
450	462.0	10,843	1,590	1,740	1,950
460	472.0	11,043	1,580	1,730	1,930
470	482.0	11,243	1,570	1,710	1,910
480	492.0	11,443	1,560	1,700	1,900
490	502.0	11,643	1,550	1,680	1,880
500	512.0	11,843	1,540	1,670	1,860
510	522.0	12,043	1,540	1,650	1,850
520	532.0	12,243	1,530	1,640	1,830
530	542.0	12,443	1,520	1,630	1,820
540	552.0	12,643	1,510	1,610	1,800
550	562.0	12,843	1,500	1,600	1,790
560	572.0	13,043	1,500	1,590	1,780
570	582.0	13,243	1,490	1,580	1,760
580	592.0	13,443	1,480	1,560	1,750
590	602.0	13,643	1,470	1,550	1,740
600	612.0	13,843	1,470	1,540	1,720

■ 7) デッキ型枠時の許容スパン (V50-1.6mm (ALB16))

軽量コン(kN/m²) ; 20 F=235 (N/mm²)

コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,085	3,010	3,920	3,690
20	32.0	2,285	2,920	3,830	3,610
30	42.0	2,485	2,840	3,750	3,510
40	52.0	2,685	2,770	3,680	3,420
50	62.0	2,885	2,700	3,620	3,340
60	72.0	3,085	2,640	3,540	3,270
70	82.0	3,285	2,590	3,470	3,200
80	92.0	3,485	2,540	3,400	3,140
90	102.0	3,685	2,490	3,340	3,080
100	112.0	3,885	2,450	3,280	3,020
110	122.0	4,085	2,410	3,230	2,970
120	132.0	4,285	2,370	3,160	2,930
130	142.0	4,485	2,330	3,090	2,880
140	152.0	4,685	2,300	3,030	2,840
150	162.0	4,885	2,270	2,960	2,800
160	172.0	5,085	2,240	2,900	2,760
170	182.0	5,285	2,210	2,850	2,730
180	192.0	5,485	2,180	2,800	2,700
190	202.0	5,685	2,150	2,750	2,660
200	212.0	5,885	2,130	2,700	2,630
210	222.0	6,085	2,110	2,650	2,600
220	232.0	6,285	2,080	2,610	2,580
230	242.0	6,485	2,060	2,570	2,550
240	252.0	6,685	2,040	2,530	2,520
250	262.0	6,885	2,020	2,500	2,500
260	272.0	7,085	2,000	2,460	2,470
270	282.0	7,285	1,980	2,430	2,450
280	292.0	7,485	1,960	2,390	2,430
290	302.0	7,685	1,950	2,360	2,410
300	312.0	7,885	1,930	2,330	2,390
310	322.0	8,085	1,910	2,300	2,370
320	332.0	8,285	1,900	2,270	2,350
330	342.0	8,485	1,880	2,250	2,330
340	352.0	8,685	1,870	2,220	2,310
350	362.0	8,885	1,860	2,200	2,290
360	372.0	9,085	1,840	2,170	2,280
370	382.0	9,285	1,830	2,150	2,260
380	392.0	9,485	1,820	2,130	2,240
390	402.0	9,685	1,800	2,100	2,230
400	412.0	9,885	1,790	2,080	2,210
410	422.0	10,085	1,780	2,060	2,200
420	432.0	10,285	1,770	2,040	2,180
430	442.0	10,485	1,760	2,020	2,170
440	452.0	10,685	1,740	2,000	2,160
450	462.0	10,885	1,730	1,980	2,140
460	472.0	11,085	1,720	1,970	2,130
470	482.0	11,285	1,710	1,950	2,120
480	492.0	11,485	1,700	1,930	2,110
490	502.0	11,685	1,690	1,910	2,090
500	512.0	11,885	1,680	1,900	2,080
510	522.0	12,085	1,670	1,880	2,070
520	532.0	12,285	1,660	1,870	2,060
530	542.0	12,485	1,660	1,850	2,050
540	552.0	12,685	1,650	1,840	2,040
550	562.0	12,885	1,640	1,820	2,030
560	572.0	13,085	1,630	1,810	2,020
570	582.0	13,285	1,620	1,800	2,010
580	592.0	13,485	1,610	1,780	1,990
590	602.0	13,685	1,610	1,770	1,980
600	612.0	13,885	1,600	1,760	1,960