

■1) デッキ型枠時の許容スパン (V5 0-1.2mm (A L B 1 2))

普通コン(kN/m ²): 24			F =235 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,131	2,740	3,650	3,390
20	32.0	2,371	2,640	3,550	3,270
30	42.0	2,611	2,560	3,430	3,170
40	52.0	2,851	2,490	3,330	3,070
50	62.0	3,091	2,420	3,250	2,990
60	72.0	3,331	2,360	3,150	2,920
70	82.0	3,571	2,310	3,040	2,850
80	92.0	3,811	2,260	2,940	2,790
90	102.0	4,051	2,210	2,850	2,730
100	112.0	4,291	2,170	2,770	2,680
110	122.0	4,531	2,130	2,700	2,630
120	132.0	4,771	2,090	2,630	2,590
130	142.0	5,011	2,060	2,560	2,550
140	152.0	5,251	2,030	2,510	2,510
150	162.0	5,491	2,000	2,450	2,470
160	172.0	5,731	1,970	2,400	2,440
170	182.0	5,971	1,940	2,350	2,400
180	192.0	6,211	1,920	2,300	2,370
190	202.0	6,451	1,890	2,260	2,340
200	212.0	6,691	1,870	2,220	2,310
210	222.0	6,931	1,850	2,180	2,290
220	232.0	7,171	1,830	2,140	2,260
230	242.0	7,411	1,810	2,110	2,230
240	252.0	7,651	1,790	2,070	2,210
250	262.0	7,891	1,770	2,040	2,190
260	272.0	8,131	1,750	2,010	2,170
270	282.0	8,371	1,730	1,980	2,150
280	292.0	8,611	1,720	1,960	2,130
290	302.0	8,851	1,700	1,930	2,110
300	312.0	9,091	1,690	1,900	2,090
310	322.0	9,331	1,670	1,880	2,070
320	332.0	9,571	1,660	1,850	2,050
330	342.0	9,811	1,650	1,830	2,030
340	352.0	10,051	1,630	1,810	2,020
350	362.0	10,291	1,620	1,790	2,000
360	372.0	10,531	1,610	1,770	1,980
370	382.0	10,771	1,590	1,750	1,950
380	392.0	11,011	1,580	1,730	1,930
390	402.0	11,251	1,570	1,710	1,910
400	412.0	11,491	1,560	1,690	1,890
410	422.0	11,731	1,550	1,670	1,870
420	432.0	11,971	1,540	1,660	1,850
430	442.0	12,211	1,530	1,640	1,840
440	452.0	12,451	1,520	1,630	1,820
450	462.0	12,691	1,510	1,610	1,800
460	472.0	12,931	1,500	1,590	1,780
470	482.0	13,171	1,490	1,580	1,770
480	492.0	13,411	1,480	1,570	1,750
490	502.0	13,651	1,470	1,550	1,740
500	512.0	13,891	1,460	1,540	1,720
510	522.0	14,131	1,450	1,530	1,710
520	532.0	14,371	1,440	1,510	1,690
530	542.0	14,611	1,430	1,500	1,680
540	552.0	14,851	1,420	1,490	1,660
550	562.0	15,091	1,410	1,480	1,650
560	572.0	15,331	1,400	1,460	1,640
570	582.0	15,571	1,380	1,450	1,620
580	592.0	15,811	1,370	1,440	1,610
590	602.0	16,051	1,360	1,430	1,600
600	612.0	16,291	1,350	1,420	1,590

■2) デッキ型枠時の許容スパン (V5 0-1.2mm (A L B 1 2))

普通コン(kN/m ²): 24			F =205 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,131	2,740	3,650	3,390
20	32.0	2,371	2,640	3,480	3,270
30	42.0	2,611	2,560	3,320	3,170
40	52.0	2,851	2,490	3,180	3,070
50	62.0	3,091	2,420	3,050	2,990
60	72.0	3,331	2,360	2,940	2,920
70	82.0	3,571	2,310	2,840	2,850
80	92.0	3,811	2,260	2,750	2,790
90	102.0	4,051	2,210	2,660	2,730
100	112.0	4,291	2,170	2,590	2,680
110	122.0	4,531	2,130	2,520	2,630
120	132.0	4,771	2,090	2,450	2,590
130	142.0	5,011	2,060	2,390	2,550
140	152.0	5,251	2,030	2,340	2,510
150	162.0	5,491	2,000	2,290	2,470
160	172.0	5,731	1,970	2,240	2,440
170	182.0	5,971	1,940	2,190	2,400
180	192.0	6,211	1,920	2,150	2,370
190	202.0	6,451	1,890	2,110	2,340
200	212.0	6,691	1,870	2,070	2,310
210	222.0	6,931	1,850	2,040	2,280
220	232.0	7,171	1,830	2,000	2,240
230	242.0	7,411	1,810	1,970	2,200
240	252.0	7,651	1,790	1,940	2,170
250	262.0	7,891	1,770	1,910	2,130
260	272.0	8,131	1,750	1,880	2,100
270	282.0	8,371	1,730	1,850	2,070
280	292.0	8,611	1,720	1,830	2,040
290	302.0	8,851	1,700	1,800	2,010
300	312.0	9,091	1,690	1,780	1,990
310	322.0	9,331	1,670	1,750	1,960
320	332.0	9,571	1,650	1,730	1,940
330	342.0	9,811	1,630	1,710	1,910
340	352.0	10,051	1,610	1,690	1,890
350	362.0	10,291	1,590	1,670	1,870
360	372.0	10,531	1,570	1,650	1,850
370	382.0	10,771	1,560	1,630	1,830
380	392.0	11,011	1,540	1,610	1,810
390	402.0	11,251	1,520	1,600	1,790
400	412.0	11,491	1,510	1,580	1,770
410	422.0	11,731	1,490	1,560	1,750
420	432.0	11,971	1,480	1,550	1,730
430	442.0	12,211	1,460	1,530	1,710
440	452.0	12,451	1,450	1,520	1,700
450	462.0	12,691	1,430	1,500	1,680
460	472.0	12,931	1,420	1,490	1,670
470	482.0	13,171	1,410	1,480	1,650
480	492.0	13,411	1,390	1,460	1,640
490	502.0	13,651	1,380	1,450	1,620
500	512.0	13,891	1,370	1,440	1,610
510	522.0	14,131	1,360	1,420	1,590
520	532.0	14,371	1,350	1,410	1,580
530	542.0	14,611	1,340	1,400	1,570
540	552.0	14,851	1,320	1,390	1,550
550	562.0	15,091	1,310	1,380	1,540
560	572.0	15,331	1,300	1,370	1,530
570	582.0	15,571	1,290	1,360	1,520
580	592.0	15,811	1,280	1,350	1,510
590	602.0	16,051	1,270	1,340	1,490
600	612.0	16,291	1,260	1,330	1,480

■3) デッキ型枠時の許容スパン (V5 0-1.6mm (A L B 1 6))

普通コン(kN/m ²): 24			F =235 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,173	2,970	3,880	3,650
20	32.0	2,413	2,870	3,780	3,550
30	42.0	2,653	2,780	3,690	3,440
40	52.0	2,893	2,700	3,610	3,340
50	62.0	3,133	2,630	3,520	3,250
60	72.0	3,373	2,560	3,440	3,170
70	82.0	3,613	2,510	3,360	3,100
80	92.0	3,853	2,450	3,290	3,030
90	102.0	4,093	2,400	3,220	2,970
100	112.0	4,333	2,360	3,150	2,920
110	122.0	4,573	2,320	3,060	2,860
120	132.0	4,813	2,280	2,990	2,820
130	142.0	5,053	2,240	2,910	2,770
140	152.0	5,293	2,210	2,850	2,730
150	162.0	5,533	2,170	2,780	2,690
160	172.0	5,773	2,140	2,730	2,650
170	182.0	6,013	2,110	2,670	2,610
180	192.0	6,253	2,090	2,620	2,580
190	202.0	6,493	2,060	2,570	2,550
200	212.0	6,733	2,040	2,520	2,520
210	222.0	6,973	2,010	2,480	2,490
220	232.0	7,213	1,990	2,440	2,460
230	242.0	7,453	1,970	2,400	2,430
240	252.0	7,693	1,950	2,360	2,410
250	262.0	7,933	1,930	2,320	2,380
260	272.0	8,173	1,910	2,290	2,360
270	282.0	8,413	1,890	2,260	2,340
280	292.0	8,653	1,870	2,230	2,310
290	302.0	8,893	1,850	2,200	2,290
300	312.0	9,133	1,840	2,170	2,270
310	322.0	9,373	1,820	2,140	2,250
320	332.0	9,613	1,810	2,110	2,230
330	342.0	9,853	1,790	2,090	2,220
340	352.0	10,093	1,780	2,060	2,200
350	362.0	10,333	1,760	2,040	2,180
360	372.0	10,573	1,750	2,010	2,160
370	382.0	10,813	1,740	1,990	2,150
380	392.0	11,053	1,720	1,970	2,130
390	402.0	11,293	1,710	1,950	2,120
400	412.0	11,533	1,700	1,930	2,100
410	422.0	11,773	1,690	1,910	2,090
420	432.0	12,013	1,680	1,890	2,070
430	442.0	12,253	1,670	1,870	2,060
440	452.0	12,493	1,660	1,850	2,050
450	462.0	12,733	1,650	1,830	2,030
460	472.0	12,973	1,630	1,820	2,020
470	482.0	13,213	1,620	1,800	2,010
480	492.0	13,453	1,620	1,780	2,000
490	502.0	13,693	1,610	1,770	1,980
500	512.0	13,933	1,600	1,750	1,960
510	522.0	14,173	1,590	1,740	1,940
520	532.0	14,413	1,580	1,720	1,930
530	542.0	14,653	1,570	1,710	1,910
540	552.0	14,893	1,560	1,700	1,900
550	562.0	15,133	1,550	1,680	1,880
560	572.0	15,373	1,540	1,670	1,870
570	582.0	15,613	1,540	1,660	1,850
580	592.0	15,853	1,530	1,640	1,840
590	602.0	16,093	1,520	1,630	1,820
600	612.0	16,333	1,510	1,620	1,810

■4) デッキ型枠時の許容スパン (V5 0-1.6mm (A L B 1 6))

普通コン(kN/m ²)； 24			F =205 (N/mm ²)		
コン厚さ	溝コン厚さ	総荷重	単純	2連続	3連続
(mm)	12	(N/m ²)	許容スパン	許容スパン	許容スパン
10	22.0	2,173	2,970	3,880	3,650
20	32.0	2,413	2,870	3,780	3,550
30	42.0	2,653	2,780	3,690	3,440
40	52.0	2,893	2,700	3,600	3,340
50	62.0	3,133	2,630	3,460	3,250
60	72.0	3,373	2,560	3,330	3,170
70	82.0	3,613	2,510	3,220	3,100
80	92.0	3,853	2,450	3,120	3,030
90	102.0	4,093	2,400	3,020	2,970
100	112.0	4,333	2,360	2,940	2,920
110	122.0	4,573	2,320	2,860	2,860
120	132.0	4,813	2,280	2,790	2,820
130	142.0	5,053	2,240	2,720	2,770
140	152.0	5,293	2,210	2,660	2,730
150	162.0	5,533	2,170	2,600	2,690
160	172.0	5,773	2,140	2,550	2,650
170	182.0	6,013	2,110	2,490	2,610
180	192.0	6,253	2,090	2,450	2,580
190	202.0	6,493	2,060	2,400	2,550
200	212.0	6,733	2,040	2,360	2,520
210	222.0	6,973	2,010	2,320	2,490
220	232.0	7,213	1,990	2,280	2,460
230	242.0	7,453	1,970	2,240	2,430
240	252.0	7,693	1,950	2,200	2,410
250	262.0	7,933	1,930	2,170	2,380
260	272.0	8,173	1,910	2,140	2,360
270	282.0	8,413	1,890	2,110	2,340
280	292.0	8,653	1,870	2,080	2,310
290	302.0	8,893	1,850	2,050	2,290
300	312.0	9,133	1,840	2,020	2,260
310	322.0	9,373	1,820	2,000	2,230
320	332.0	9,613	1,810	1,970	2,200
330	342.0	9,853	1,790	1,950	2,180
340	352.0	10,093	1,780	1,920	2,150
350	362.0	10,333	1,760	1,900	2,130
360	372.0	10,573	1,750	1,880	2,100
370	382.0	10,813	1,740	1,860	2,080
380	392.0	11,053	1,720	1,840	2,060
390	402.0	11,293	1,710	1,820	2,030
400	412.0	11,533	1,700	1,800	2,010
410	422.0	11,773	1,690	1,780	1,990
420	432.0	12,013	1,680	1,760	1,970
430	442.0	12,253	1,670	1,750	1,950
440	452.0	12,493	1,660	1,730	1,930
450	462.0	12,733	1,650	1,710	1,920
460	472.0	12,973	1,630	1,700	1,900
470	482.0	13,213	1,620	1,680	1,880
480	492.0	13,453	1,620	1,670	1,860
490	502.0	13,693	1,600	1,650	1,850
500	512.0	13,933	1,590	1,640	1,830
510	522.0	14,173	1,580	1,620	1,810
520	532.0	14,413	1,560	1,610	1,800
530	542.0	14,653	1,550	1,600	1,780
540	552.0	14,893	1,540	1,580	1,770
550	562.0	15,133	1,520	1,570	1,760
560	572.0	15,373	1,510	1,560	1,740
570	582.0	15,613	1,500	1,550	1,730
580	592.0	15,853	1,490	1,530	1,720
590	602.0	16,093	1,480	1,520	1,700
600	612.0	16,333	1,470	1,510	1,690