

■1) デッキ型枠時の許容スパン (V5 0A-1.2mm (ALF12))

普通コン (kN/m <sup>2</sup> ): 24		F=205 (N/mm <sup>2</sup> )			
コン厚さ	溝コ厚さ	総荷重	単純	2連続	3連続
(mm)	24	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	34.0	2,419	2,820	3,730	3,490
20	44.0	2,659	2,730	3,650	3,380
30	54.0	2,899	2,650	3,560	3,280
40	64.0	3,139	2,580	3,460	3,200
50	74.0	3,379	2,520	3,340	3,120
60	84.0	3,619	2,460	3,220	3,050
70	94.0	3,859	2,410	3,120	2,980
80	104.0	4,099	2,360	3,030	2,920
90	114.0	4,339	2,320	2,940	2,870
100	124.0	4,579	2,280	2,870	2,820
110	134.0	4,819	2,240	2,790	2,770
120	144.0	5,059	2,200	2,730	2,720
130	154.0	5,299	2,170	2,660	2,680
140	164.0	5,539	2,140	2,600	2,640
150	174.0	5,779	2,110	2,550	2,610
160	184.0	6,019	2,080	2,500	2,570
170	194.0	6,259	2,050	2,450	2,540
180	204.0	6,499	2,030	2,400	2,510
190	214.0	6,739	2,000	2,360	2,480
200	224.0	6,979	1,980	2,320	2,450
210	234.0	7,219	1,960	2,280	2,420
220	244.0	7,459	1,940	2,240	2,390
230	254.0	7,699	1,920	2,210	2,370
240	264.0	7,939	1,900	2,170	2,340
250	274.0	8,179	1,880	2,140	2,320
260	284.0	8,419	1,860	2,110	2,300
270	294.0	8,659	1,840	2,080	2,280
280	304.0	8,899	1,820	2,050	2,260
290	314.0	9,139	1,810	2,030	2,240
300	324.0	9,379	1,790	2,000	2,220
310	334.0	9,619	1,780	1,980	2,200
320	344.0	9,859	1,760	1,950	2,180
330	354.0	10,099	1,750	1,930	2,160
340	364.0	10,339	1,740	1,910	2,130
350	374.0	10,579	1,720	1,880	2,110
360	384.0	10,819	1,710	1,860	2,080
370	394.0	11,059	1,700	1,840	2,060
380	404.0	11,299	1,680	1,820	2,040
390	414.0	11,539	1,670	1,800	2,020
400	424.0	11,779	1,660	1,780	2,000
410	434.0	12,019	1,650	1,770	1,980
420	444.0	12,259	1,640	1,750	1,960
430	454.0	12,499	1,630	1,730	1,940
440	464.0	12,739	1,620	1,720	1,920
450	474.0	12,979	1,610	1,700	1,900
460	484.0	13,219	1,600	1,680	1,880
470	494.0	13,459	1,590	1,670	1,870
480	504.0	13,699	1,580	1,650	1,850
490	514.0	13,939	1,570	1,640	1,830
500	524.0	14,179	1,560	1,630	1,820
510	534.0	14,419	1,550	1,610	1,800
520	544.0	14,659	1,540	1,600	1,790
530	554.0	14,899	1,540	1,590	1,770
540	564.0	15,139	1,530	1,570	1,760
550	574.0	15,379	1,520	1,560	1,750
560	584.0	15,619	1,510	1,550	1,730
570	594.0	15,859	1,500	1,540	1,720
580	604.0	16,099	1,500	1,530	1,710
590	614.0	16,339	1,490	1,510	1,690
600	624.0	16,579	1,480	1,500	1,680

■2) デッキ型枠時の許容スパン (V5 0A-1.6mm (ALF16))

普通コン (kN/m <sup>2</sup> ): 24		F=205 (N/mm <sup>2</sup> )			
コン厚さ	溝コ厚さ	総荷重	単純	2連続	3連続
(mm)	24	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	34.0	2,461	3,060	3,970	3,740
20	44.0	2,701	2,970	3,880	3,650
30	54.0	2,941	2,890	3,800	3,570
40	64.0	3,181	2,810	3,730	3,480
50	74.0	3,421	2,740	3,660	3,390
60	84.0	3,661	2,680	3,600	3,320
70	94.0	3,901	2,630	3,520	3,250
80	104.0	4,141	2,570	3,450	3,180
90	114.0	4,381	2,530	3,390	3,120
100	124.0	4,621	2,480	3,330	3,070
110	134.0	4,861	2,440	3,270	3,020
120	144.0	5,101	2,400	3,220	2,970
130	154.0	5,341	2,360	3,170	2,920
140	164.0	5,581	2,330	3,130	2,880
150	174.0	5,821	2,300	3,080	2,840
160	184.0	6,061	2,270	3,040	2,800
170	194.0	6,301	2,240	3,000	2,770
180	204.0	6,541	2,210	2,960	2,730
190	214.0	6,781	2,180	2,930	2,700
200	224.0	7,021	2,160	2,890	2,670
210	234.0	7,261	2,130	2,860	2,640
220	244.0	7,501	2,110	2,830	2,610
230	254.0	7,741	2,090	2,790	2,580
240	264.0	7,981	2,070	2,740	2,560
250	274.0	8,221	2,050	2,700	2,530
260	284.0	8,461	2,030	2,670	2,510
270	294.0	8,701	2,010	2,630	2,480
280	304.0	8,941	1,990	2,590	2,460
290	314.0	9,181	1,970	2,560	2,440
300	324.0	9,421	1,960	2,530	2,420
310	334.0	9,661	1,940	2,490	2,400
320	344.0	9,901	1,920	2,460	2,380
330	354.0	10,141	1,910	2,430	2,360
340	364.0	10,381	1,890	2,410	2,340
350	374.0	10,621	1,880	2,380	2,320
360	384.0	10,861	1,870	2,350	2,310
370	394.0	11,101	1,850	2,330	2,290
380	404.0	11,341	1,840	2,300	2,270
390	414.0	11,581	1,830	2,280	2,260
400	424.0	11,821	1,810	2,250	2,240
410	434.0	12,061	1,800	2,230	2,230
420	444.0	12,301	1,790	2,210	2,210
430	454.0	12,541	1,780	2,190	2,200
440	464.0	12,781	1,770	2,170	2,180
450	474.0	13,021	1,760	2,150	2,170
460	484.0	13,261	1,740	2,130	2,160
470	494.0	13,501	1,730	2,110	2,140
480	504.0	13,741	1,720	2,090	2,130
490	514.0	13,981	1,710	2,070	2,120
500	524.0	14,221	1,700	2,060	2,110
510	534.0	14,461	1,700	2,040	2,100
520	544.0	14,701	1,690	2,020	2,080
530	554.0	14,941	1,680	2,000	2,070
540	564.0	15,181	1,670	1,990	2,060
550	574.0	15,421	1,660	1,970	2,050
560	584.0	15,661	1,650	1,960	2,040
570	594.0	15,901	1,640	1,940	2,030
580	604.0	16,141	1,630	1,930	2,020
590	614.0	16,381	1,630	1,910	2,010
600	624.0	16,621	1,620	1,900	2,000

■3) デッキ型枠時の許容スパン (V5 0A-1.2mm (ALF12))

軽量コン (kN/m <sup>2</sup> ): 20		F=205 (N/mm <sup>2</sup> )			
コン厚さ	溝コ厚さ	総荷重	単純	2連続	3連続
(mm)	24	(N/m <sup>2</sup> )	許容スパン	許容スパン	許容スパン
10	34.0	2,283	2,870	3,790	3,550
20	44.0	2,483	2,800	3,710	3,460
30	54.0	2,683	2,720	3,640	3,370
40	64.0	2,883	2,660	3,570	3,290
50	74.0	3,083	2,600	3,490	3,210
60	84.0	3,283	2,550	3,380	3,150
70	94.0	3,483	2,500	3,290	3,090
80	104.0	3,683	2,450	3,200	3,030
90	114.0	3,883	2,410	3,110	2,980
100	124.0	4,083	2,370	3,030	2,930
110	134.0	4,283	2,330	2,960	2,880
120	144.0	4,483	2,290	2,900	2,840
130	154.0	4,683	2,260	2,830	2,800
140	164.0	4,883	2,230	2,770	2,760
150	174.0	5,083	2,200	2,720	2,720
160	184.0	5,283	2,170	2,670	2,690
170	194.0	5,483	2,150	2,620	2,650
180	204.0	5,683	2,120	2,570	2,620
190	214.0	5,883	2,100	2,530	2,590
200	224.0	6,083	2,070	2,490	2,560
210	234.0	6,283	2,050	2,450	2,530
220	244.0	6,483	2,030	2,410	2,510
230	254.0	6,683	2,010	2,370	2,480
240	264.0	6,883	1,990	2,340	2,460
250	274.0	7,083	1,970	2,300	2,440
260	284.0	7,283	1,950	2,270	2,410
270	294.0	7,483	1,930	2,240	2,390
280	304.0	7,683	1,920	2,210	2,370
290	314.0	7,883	1,900	2,180	2,350
300	324.0	8,083	1,880	2,160	2,330
310	334.0	8,283	1,870	2,130	2,310
320	344.0	8,483	1,850	2,100	2,290
330	354.0	8,683	1,840	2,080	2,280
340	364.0	8,883	1,830	2,060	2,260
350	374.0	9,083	1,810	2,030	2,240
360	384.0	9,283	1,800	2,010	2,220
370	394.0	9,483	1,790	1,990	2,210
380	404.0	9,683	1,770	1,970	2,190
390	414.0	9,883	1,760	1,950	2,180
400	424.0	10,083	1,750	1,930	2,160
410	434.0	10,283	1,740	1,910	2,140
420	444.0	10,483	1,730	1,890	2,120
430	454.0	10,683	1,720	1,870	2,100
440	464.0	10,883	1,710	1,860	2,080
450	474.0	11,083	1,700	1,840	2,060
460	484.0	11,283	1,690	1,820	2,040
470	494.0	11,483	1,680	1,810	2,020
480	504.0	11,683	1,670	1,790	2,000
490	514.0	11,883	1,660	1,780	1,990
500	524.0	12,083	1,650	1,760	1,970
510	534.0	12,283	1,640	1,750	1,950
520	544.0	12,483	1,630	1,730	1,940
530	554.0	12,683	1,620	1,720	1,920
540	564.0	12,883	1,610	1,710	1,910
550	574.0	13,083	1,600	1,690	1,890
560	584.0	13,283	1,600	1,680	1,880
570	594.0	13,483	1,590	1,670	1,870
580	604.0	13,683	1,580	1,660	1,850
590	614.0	13,883	1,570	1,640	1,840
600	624.0	14,083	1,570	1,630	1,820

■4) デッキ型枠時の許容スパン (V5 0A-1.6mm (ALF16))

軽量コン (kN/m <sup>2</sup> ): 20		F=205 (N/mm <sup></sup>			
-------------------------------	--	-------------------------	--	--	--